

/plan

Delegate planning to the plan agent: `/plan`

`/plan help`

Overview

`/plan` hands a task description to the plan agent, which performs read-only codebase analysis and returns a plan for the requested work. The current session delegates the description verbatim and waits for the plan agent to report back; the plan agent cannot edit files.

The plan agent's output is analysis, not implementation. Implementation happens in your normal session after you review the plan - the help text notes that an approval prompt precedes any implementation step.

Syntax

`/plan <task description>`

`/plan help`

An empty description or the `help` token prints the usage line instead of delegating.

Options / Subcommands

Form	Description
<code>/plan <task description></code>	Delegate the description to the plan agent
<code>/plan help</code>	Print usage help

Examples

Plan a feature:

`/plan add retry with exponential backoff to the HTTP client`

Plan a refactor:

`/plan split the provider registry into per-provider modules`

Plan an investigation:

`/plan find why the compaction test flakes on CI and propose a fix`

Check the usage line:

`/plan help`

Plan with explicit scope constraints in the description:

`/plan redesign the permission check pipeline, touch only crates/ragent-agent/src/session`

Output

- The delegation is recorded in the transcript; the plan agent runs and its report streams into the message window as the plan agent completes.
- Empty input or `help` prints the usage line: `Usage: /plan <task description>` (with the note that implementation follows an approval prompt).
- The current session remains usable after the plan returns; no mode change occurs.

Related

- `plan_enter` - the underlying sub-agent delegation used by `/plan`
- `/mode architect` - switch role mode without delegating
- `/agent` - switch the session's agent entirely
- `/loop` - goal-driven loop execution for carrying a plan out