

/reload

“Reload configuration, agents, MCP servers, and skills” (SlashCommandDef, crates/ragent-tui/src/app/state.rs).

Overview

/reload re-reads runtime configuration into the running TUI without a restart. With no argument it reloads everything (config, agents, MCP servers, and skills); a subcommand narrows the scope to a single subsystem. Results accumulate into one From: /reload report block, one status line per subsystem, with per-subsystem success ([ok]) or failure ([x]) markers.

The handler is the reload arm in crates/ragent-tui/src/app/slash.rs (approximately lines 3727-3915). As part of every reload the bash allow/deny lists and directory lists are also refreshed from config.

Syntax

```
/reload [all|config|mcp|skills|agents]
```

The first argument defaults to all when omitted.

Options / Subcommands

Form	Description
/reload	Reload everything (config + agents + MCP + skills)
/reload all	Same as bare /reload
/reload config	Re-read ragent.json, refresh provider detection, selected model, context window, thinking level, code index flag, and tool visibility
/reload agents	Rebuild the builtin and custom agent list, preserving the current selection
/reload mcp	Rebuild the MCP server display list from config, preserving connected status and tools
/reload skills	Confirm skills are re-read from disk on next use (no persistent cache)
/reload help, /reload --help, /reload -h	Show the help table

Examples

Reload everything

```
/reload
```

Output:

```
From: /reload
[ok] Config reloaded (ragent.json)
[ok] Agents reloaded - 3 custom agent(s) (was 3)
[ok] MCP reloaded - 2 server(s) in config (was 2)
```

[ok] Skills will be reloaded from disk on next use (no cache to clear)

Reload configuration only

/reload config

Output:

From: /reload

[ok] Config reloaded (ragent.json)

This refreshes provider detection, the selected model and its context window, the thinking level, code_index_enabled, tool visibility, and the bash and directory lists.

Reload agents only

/reload agents

Output:

From: /reload

[ok] Agents reloaded - 4 custom agent(s) (was 3)

Custom agents are rebuilt from the agent directories; when two definitions collide on a name the later one is renamed to custom:<name> and a diagnostic is logged. The currently selected agent is preserved when it still exists after the rebuild.

Reload MCP servers only

/reload mcp

Output:

From: /reload

[ok] MCP reloaded - 2 server(s) in config (was 2)

The display list is rebuilt from the mcp section of Config::load(). Each server keeps its previous connected status and tool list when it existed before the reload; new entries start disabled.

Reload skills only

/reload skills

Output:

From: /reload

[ok] Skills will be reloaded from disk on next use (no cache to clear)

Show help

/reload help

Output: the help table listing the all|config|mcp|skills|agents forms.

Output

- All output accumulates under a single From: /reload header; each subsystem contributes one [ok] ... (success) or [x] ... reload failed: <error> (failure) line.
- Config reload failure emits [x] Config reload failed: <error> and logs reload config failed: <error>.
- An unknown subcommand appends Unknown subcommand '<name>'. Usage: /reload [all|config|mcp|skills|agents] to the report.
- The status line is set to reload.
- Unconditionally after any /reload invocation, the bash lists (ragent_agent::bash_lists::load_from_config()) and directory lists (ragent_agent::dir_lists::load_from_config()) are refreshed from config.

Related

- /config show - inspect what will be reloaded
- /config save - back up the config before editing it
- /mcp - view the MCP server list after /reload mcp
- /skills - view the skill registry