

/swarm

Auto-decompose a goal into parallel subtasks (/swarm | /swarm status | /swarm help)

Overview

/swarm takes a goal prompt and asks the configured model to decompose it into parallel subtasks that are then executed by teammates. It is the quickest way to fan a large piece of work out across a team without hand-writing the task list: the model proposes the decomposition, and the swarm runtime drives the subtasks from there.

An optional `--agent <type>` prefix sets the default agent type used for the decomposed subtasks.

Syntax

```
/swarm <prompt>
/swarm --agent <type> <prompt>
/swarm status
/swarm cancel
/swarm help
```

Options / Subcommands

Form	Description
/swarm <prompt>	Decomposes the prompt into subtasks and starts the swarm.
--agent <type>	Optional prefix flag; sets the default agent type for the subtasks.
status	Shows current swarm progress.
cancel	Cancels the active swarm.
help	Prints usage.

Guards

- Starting a second swarm while one is active is refused: [warn] A swarm is already active - use /swarm cancel first
- Starting a swarm without a configured model is refused: [warn] /swarm requires a configured model - use /model

Examples

```
/swarm Refactor the config parser and update every caller in the tests
/swarm --agent coder Split the migration into per-crate tasks and run them
/swarm status
/swarm cancel
/swarm help
```

Output

- On start, the status line shows `[wait] swarm: decomposing goal...` while the decomposition request is in flight.
- Decomposition is an asynchronous LLM call: the command returns immediately and the decomposed subtasks are reported as the model produces them.
- `/swarm status` reports the running swarm's progress.
- `/swarm cancel` stops the active swarm, after which a new `/swarm` can be started.

Notes

- A model must be selected before a swarm can start (`/model`).
- The decomposed subtasks run as teammates; use `/team tasks` to watch the shared task list fill up, and `/swarm status` for swarm-level progress.
- Only one swarm may be active at a time.

Related

- `/team` – team lifecycle commands for the teammates a swarm creates
- `/blueprints` – list installed team blueprints
- `/model` – required before a swarm can start
- `docs/howtos/teams.md` – teams and swarm how-to manual