

/template

List and apply reusable prompt templates: `/template [name] [args]`

Overview

`/template` lists reusable prompt templates discovered from two directories - `~/.ragent/templates/` (personal) and `.ragent/templates/` (project) - and applies them by name. Templates are markdown files with `{{placeholder}}` variables such as `{{title}}`, `{{description}}`, and `{{arguments}}`.

Applying a template substitutes `{{arguments}}` with the args you pass and then **overwrites the input buffer** with the result: any text you had already typed into the prompt input is replaced. The applied text is shown first in a fenced block so you can see exactly what landed in the input.

Syntax

```
/template                # list all templates
/template <name>          # apply a template, {{arguments}} empty
/template <name> <args>   # apply with {{arguments}} substituted
/template help
```

Options / Subcommands

Form	Description
<code>/template</code>	List all templates in a Name Description Scope Placeholders table
<code>/template <name></code>	Apply the template; <code>{{arguments}}</code> stays empty
<code>/template <name> <args></code>	Apply with <code><args></code> substituted into <code>{{arguments}}</code>
<code>/template help</code>	Print usage help

Unknown `<name>` prints the sorted list of available template names plus usage.

Examples

List available templates:

```
/template
```

Apply a review template:

```
/template review-checklist
```

Apply with arguments:

```
/template release-notes v1.0.96
```

Apply a bug-report template with structured args:

```
/template bugreport "test_loop_termination flakes" --since 2026-09-01
```

Check the usage help:

`/template help`

Output

Bare form: a markdown table sorted by name with the columns Name | Description | Scope | Placeholders. When no templates are found, the output explains where to create them:

- `~/ .ragent/templates/` - personal templates
- `.ragent/templates/` - project templates (higher priority)
- placeholders use the `{{name}}` form, e.g. `{{title}}`, `{{description}}`, `{{arguments}}`

Applied template: the rendered text is shown in a fenced block, followed by the placeholder list and three numbered next-step options. The input buffer is then set to the rendered text and the cursor moved to its end - anything you had typed before running the command is replaced.

Unknown name:

Template '`<name>`' not found.

followed by the sorted list of available names and the usage line.

Related

- `/reload` - rescan configuration and skills (restart picks up new template files)
- `~/ .ragent/templates/` - personal template directory
- `.ragent/templates/` - project template directory (higher priority)
- `/history` - reuse previous inputs as an alternative to templates