

/model

Switch the active model, or show metadata with `/model show` (`/model help` for usage)

Overview

`/model` manages the active LLM model selection in the TUI. With no arguments it opens the model picker for the currently configured provider; when no provider is configured it falls back to the provider picker. `/model show` prints a metadata report for the active model into the message window. Switching models happens through the interactive picker dialogs rather than by typing a model name on the command line.

Syntax

<code>/model</code>	Open the model picker for the configured provider
<code>/model show</code>	Print the active model's metadata report
<code>/model help</code>	Show the help table

Options / Subcommands

Form	Description
<code>/model</code>	Open the model picker for the configured provider (or the provider picker when none is configured)
<code>/model show</code>	Print the active model's metadata report into the chat
<code>/model help</code>	Show the help table

Any other argument produces the usage line `Usage: /model [show]`.

Bare-form branches

The bare `/model` form takes three branches depending on the configured provider:

1. **Normal provider configured** - the model list for that provider is fetched (the status line shows a model-discovery progress state) and the model picker opens with the discovered entries.
2. **azure_resource provider configured** - an Azure resource entry picker opens instead of the model list. The previously selected resource is pre-highlighted from the `azure_resource_last_selection` storage setting.
3. **router provider configured** - the model-router setup dialog opens, seeded from the configured concrete providers. If no concrete providers are configured, the provider picker opens instead.

If nothing is configured at all, branch 1 becomes the provider picker so the first `/model` call walks you straight into provider setup.

Examples

```
/model
```

Opens the model picker for the configured provider.

```
/model show
```

Prints the metadata report of the currently active model (context window, token limits, capabilities) into the message window.

```
/model help
```

Prints the three-row subcommand table shown above.

```
/model list
```

Not a supported form - prints Usage: `/model [show]` in the status bar.

Output

- Bare form: no chat text; the TUI switches to a model-discovery status and then the picker dialog (LoadingModels step while the provider's model list is fetched, then the selection list).
- `/model show`: the metadata report appended to the message window, with the status line `active model metadata`. If no model is active, the status line shows `[warn] No active model selected` instead.
- `/model help`: the help table appended to the message window with status `model: help`.
- Unknown argument: status line Usage: `/model [show]`.

Related

- `/thinking` - switch the thinking level of the selected model
- `/provider` - change or show provider configuration
- `/provider_reset` - reset the current provider and stored credentials
- `/router` - manage the model-router cluster
- `ragent models` - CLI equivalent that lists available models