

Tools — GitLab

Native GitLab tools for issues, merge requests, pipelines, and jobs. Requires `/gitlab` setup authentication and a GitLab-backed git remote.

Tool	Description
<code>gitlab_list_issues</code>	List issues.
<code>gitlab_get_issue</code>	Get issue details.
<code>gitlab_create_issue</code>	Create an issue.
<code>gitlab_comment_issue</code>	Comment on an issue.
<code>gitlab_close_issue</code>	Close an issue.
<code>gitlab_list_mrs</code>	List merge requests.
<code>gitlab_get_mr</code>	Get MR details.
<code>gitlab_create_mr</code>	Create a merge request.
<code>gitlab_merge_mr</code>	Merge an MR.
<code>gitlab_approve_mr</code>	Approve an MR.
<code>gitlab_list_pipelines</code>	List pipelines.
<code>gitlab_get_pipeline</code>	Get pipeline details.
<code>gitlab_list_jobs</code>	List jobs in a pipeline.
<code>gitlab_get_job</code>	Get job details.
<code>gitlab_get_job_log</code>	Get job log output.
<code>gitlab_retry_job</code>	Retry a failed job.
<code>gitlab_cancel_job</code>	Cancel a running job.
<code>gitlab_retry_pipeline</code>	Retry a pipeline.
<code>gitlab_cancel_pipeline</code>	Cancel a pipeline.

Visibility switch: `gitlab`.

`gitlab_list_issues`

Arguments

Argument	Type	Required	Description	Typical value
<code>state</code>	enum	no	opened (default), closed, all	"opened"
<code>labels</code>	string	no	Comma-separated label names	"bug"

`gitlab_get_issue` / `gitlab_close_issue`

Get full issue details, or close an issue.

Arguments

Argument	Type	Required	Description
iid	integer	yes	Issue internal ID (project-scoped)
comment	string	no (close)	Closing note posted before closing

gitlab_create_issue

Arguments

Argument	Type	Required	Description	Typical value
title	string	yes	Issue title	"Pipeline failing on main"
description	string	no	Description in markdown	—
labels	string	no	Comma-separated labels	"bug"

gitlab_comment_issue

Argument	Type	Required	Description
iid	integer	yes	Issue internal ID
body	string	yes	Comment text

gitlab_list_mrs

Arguments

Argument	Type	Required	Description	Typical value
state	enum	no	opened (default), merged, closed, all	"opened"
target_branch	string	no	Filter by target branch	"main"

gitlab_get_mr

Argument	Type	Required	Description
iid	integer	yes	Merge request internal ID

gitlab_create_mr

Arguments

Argument	Type	Required	Description	Typical value
title	string	yes	MR title	"Add greet subcommand"
source_branch	string	yes	Source branch	"feature/greet"
target_branch	string	yes	Target branch	"main"
description	string	no	Description in markdown	—

gitlab_merge_mr / gitlab_approve_mr

Argument	Type	Required	Description
iid	integer	yes	Merge request internal ID

gitlab_list_pipelines / gitlab_get_pipeline

Argument	Type	Required	Description	Typical value
status	enum	no (list)	running, pending, success, failed, canceled	"failed"
id	integer	yes (get)	Pipeline ID	—

gitlab_list_jobs / gitlab_get_job / gitlab_get_job_log

Argument	Type	Required	Description
pipeline_id	integer	yes (list_jobs)	Pipeline to list jobs for
job_id	integer	yes (get_job, get_job_log)	Job ID

gitlab_get_job_log returns the job's trace output (may be large).

gitlab_retry_job / gitlab_cancel_job / gitlab_retry_pipeline / gitlab_cancel_pipeline

Argument	Type	Required	Description
job_id	integer	yes (job tools)	Job ID
pipeline_id	integer	yes (pipeline tools)	Pipeline ID

Example:

```
gitlab_list_pipelines status="failed"
gitlab_list_jobs pipeline_id=12345
gitlab_get_job_log job_id=67890
gitlab_retry_job job_id=67890
```