

Tools — Interactive

Ask the user questions, record reasoning notes, evaluate expressions, and read environment variables.

Tool	Description
<code>ask_user</code>	Ask the user a question (with optional choices).
<code>think</code>	Record a short reasoning note.
<code>calculator</code>	Evaluate a mathematical expression.
<code>get_env</code>	Read environment variable values.

`ask_user`

Ask the user a question and wait for the typed response. With `options` the user picks from a multiple-choice dialog; otherwise they type free text.

Arguments

Argument	Type	Required	Description	Typical value
<code>question</code>	string	yes	The prompt shown to the user	"Which build profile?"
<code>options</code>	array	no	Fixed choices; the returned value will be one of these strings	["Debug", "Release", "Check only"]

Example:

```
ask_user question="Which build profile?" options=["Debug","Release","Check only"]
```

`think`

Record a short reasoning note in the session log without changing project state (published as a reasoning event). Keep entries brief and focused on the next action.

Arguments

Argument	Type	Required	Description
<code>thought</code>	string	yes	Short reasoning note

Example: `think thought="Retrying the edit with the verbatim needle from line 42."`

calculator

Evaluate a mathematical expression (Python arithmetic + the `math` module; integer/float/complex). Runs in a short-lived `python3` process with a 10-second timeout.

Arguments

Argument	Type	Required	Description	Typical value
<code>expression</code>	string	yes	Python-syntax expression	<code>"math.factorial(20)"</code> , <code>"2 ** 32"</code>

Example: `calculator expression="math.sqrt(2 * math.pi)"`

get_env

Read one or more environment variables. Names containing `KEY`, `SECRET`, `TOKEN`, `PASSWORD` (or similar) are redacted to avoid leaking credentials.

Arguments

Argument	Type	Required	Description
<code>name</code>	string	one of two	Single variable name
<code>names</code>	array	one of two	List of variable names

Example: `get_env name="HOME"`