/bug-report

Generate a bug report file with session diagnostics, logs, and transcript

Overview

`/bug-report` writes a self-contained markdown bug report under the project working directory so it can be attached to an issue. The file is created at `log/bug-report-<YYYYMMDD>-<HHMMSS>.md` (the `log/` directory is created if missing). Sensitive content is redacted: log entries and the transcript pass through `redact_secrets`, and transcript messages are truncated.

There are no subcommands; the command runs immediately.

Syntax

```
/bug-report
```

Options / Subcommands

Form	Description
(bare)	Write the bug report and print its path

Report contents

Section	What it contains
Session Information	Session id, title, directory, created/updated timestamps
Agent Configuration	Active agent, its description, selected model
Tool Configuration	**Registered** tool count (`ToolRegistry::list()`, the size of the whole surface) followed by the number of enabled family switches and per-family visibility (github, gitlab, teams, agents, plan, codeindex, masterfetch)
Token Usage	Input, output, and total token counts for the session
Recent Log Entries	Last 50 log lines, `redact_secrets` applied
Session Transcript	Each message, redacted, truncated to 501 characters

Examples

```
From: /bug-report
Bug report written to log/bug-report-20260911-141530.md

The report includes session info, agent and tool configuration, token usage,
the last 50 log entries, and the session transcript.
Please review the report for sensitive information before sharing.
```

```
From: /bug-report
(In a session with 3 messages and one tool error)
The transcript section shows each message redacted and truncated to 501
characters; the log section shows the tool error with secrets redacted.
```

Output

One success block in the message window: the written file path, a summary of what the report includes, and a warning to review the file for sensitive information before sharing it. Failures (unwritable path) print a `[warn]` error line.

Related

- `/doctor` - live environment diagnostics instead of a file report
- `/log` - the in-session log panel
- Log directory `log/` also holds sub-agent reports