Tools — GitLab

Native GitLab tools for issues, merge requests, pipelines, and jobs. Requires `/gitlab setup` authentication and a GitLab-backed git remote.

Tool	Description
`gitlab_list_issues`	List issues.
`gitlab_get_issue`	Get issue details.
`gitlab_create_issue`	Create an issue.
`gitlab_comment_issue`	Comment on an issue.
`gitlab_close_issue`	Close an issue.
`gitlab_list_mrs`	List merge requests.
`gitlab_get_mr`	Get MR details.
`gitlab_create_mr`	Create a merge request.
`gitlab_merge_mr`	Merge an MR.
`gitlab_approve_mr`	Approve an MR.
`gitlab_list_pipelines`	List pipelines.
`gitlab_get_pipeline`	Get pipeline details.
`gitlab_list_jobs`	List jobs in a pipeline.
`gitlab_get_job`	Get job details.
`gitlab_get_job_log`	Get job log output.
`gitlab_retry_job`	Retry a failed job.
`gitlab_cancel_job`	Cancel a running job.
`gitlab_retry_pipeline`	Retry a pipeline.
`gitlab_cancel_pipeline`	Cancel a pipeline.

Visibility switch: `gitlab`.

---

gitlab_list_issues

Arguments

Argument	Type	Required	Description	Typical value
`state`	enum	no	`opened` (default), `closed`, `all`	`"opened"`
`labels`	string	no	Comma-separated label names	`"bug"`

---

gitlab_get_issue / gitlab_close_issue

Get full issue details, or close an issue.

Arguments

Argument	Type	Required	Description
`iid`	integer	yes	Issue internal ID (project-scoped)
`comment`	string	no (close)	Closing note posted before closing

---

gitlab_create_issue

Arguments

Argument	Type	Required	Description	Typical value
`title`	string	yes	Issue title	`"Pipeline failing on main"`
`description`	string	no	Description in markdown	—
`labels`	string	no	Comma-separated labels	`"bug"`

---

gitlab_comment_issue

Argument	Type	Required	Description
`iid`	integer	yes	Issue internal ID
`body`	string	yes	Comment text

---

gitlab_list_mrs

Arguments

Argument	Type	Required	Description	Typical value
`state`	enum	no	`opened` (default), `merged`, `closed`, `all`	`"opened"`
`target_branch`	string	no	Filter by target branch	`"main"`

---

gitlab_get_mr

Argument	Type	Required	Description
`iid`	integer	yes	Merge request internal ID

---

gitlab_create_mr

Arguments

Argument	Type	Required	Description	Typical value
`title`	string	yes	MR title	`"Add greet subcommand"`
`source_branch`	string	yes	Source branch	`"feature/greet"`
`target_branch`	string	yes	Target branch	`"main"`
`description`	string	no	Description in markdown	—

---

gitlab_merge_mr / gitlab_approve_mr

Argument	Type	Required	Description
`iid`	integer	yes	Merge request internal ID

---

gitlab_list_pipelines / gitlab_get_pipeline

Argument	Type	Required	Description	Typical value
`status`	enum	no (`list`)	`running`, `pending`, `success`, `failed`, `canceled`	`"failed"`
`pipeline_id`	integer	yes (`get`)	Pipeline ID (the global ID from the pipeline URL, not an IID)	—

---

gitlab_list_jobs / gitlab_get_job / gitlab_get_job_log

Argument	Type	Required	Description
`pipeline_id`	integer	yes (`list_jobs`)	Pipeline to list jobs for
`job_id`	integer	yes (`get_job`, `get_job_log`)	Job ID

`gitlab_get_job_log` returns the job's trace output (may be large).

---

gitlab_retry_job / gitlab_cancel_job / gitlab_retry_pipeline / gitlab_cancel_pipeline

Argument	Type	Required	Description
`job_id`	integer	yes (job tools)	Job ID
`pipeline_id`	integer	yes (pipeline tools)	Pipeline ID

Example:

```
gitlab_list_pipelines status="failed"
gitlab_list_jobs pipeline_id=12345
gitlab_get_job_log job_id=67890
gitlab_retry_job job_id=67890
```