Slash Command Howtos

Per-command reference documents for the ragent TUI slash commands. Each document describes the command, every subcommand and option the dispatcher implements, and worked examples. Typing `/` in the TUI opens the autocomplete menu, and `/<command> help` prints per-command help where the handler supports it.

Commands

Command	Document	Summary
`/about`	about	Show application info, version, and authors
`/agent`	agent	Switch the active agent: /agent [] | /agent help
`/agents`	agents	List all agents - built-in and custom
`/browse_refresh`	browse_refresh	Refresh the @ file-picker project index
`/bench`	bench	Benchmark runner: /bench list|init |show|run |status|open last|cancel
`/backend`	backend	Execution backend: /backend [] - open the switcher, or switch to a kind
`/automation`	automation	Automation service: /automation [list] - runs , run , help
`/clear`	clear	Clear message history for the current session
`/clip`	clip	Copy the rendered message-window contents to the system clipboard
`/cancel`	cancel	Cancel a background task (/cancel | /cancel help)
`/config`	config	Configuration: /config show|save|list|help
`/context`	context	Manage context cache: /context refresh | /context help
`/cron`	cron	Schedule agent runs: /cron add “”|re-move|enable|disable|list|log|help
`/compact`	compact	Summarise and compact the conversation history
`/inbox`	inbox	Triage inbox: /inbox list|claim |dismiss |clear|help
`/cost`	cost	Show session token usage and estimated cost
`/help`	help	Show available slash commands

Command	Document	Summary
`/history`	history	Browse and re-use previous inputs; /history [filter] restricts to matching entries (arrow keys to select, Enter to insert, c to copy to clipboard); /history help
`/inputdiag`	inputdiag	Dump input/cursor/selection diagnostics for troubleshooting
`/log`	log	Log panel: /log [clear sub-agents|panics|research|editlog|help]
`/loop`	loop	Goal-driven agent loop: /loop opens setup, /loop starts, /loop help shows usage
`/profile`	profile	Toggle the agent-loop profiler panel (/profile on|off|help)
`/perf`	perf	Alias for /profile - toggle the agent-loop perf panel (/perf on|off|help)
`/llmstats`	llmstats	Show average LLM response time and token throughput
`/model`	model	Switch the active model, or show metadata with /model show (/model help for usage)
`/thinking`	thinking	Switch the current thinking level: /thinking auto|off|low|medium|high
`/provider`	provider	Change provider, show config, or configure model router: /provider [show|router|help]
`/provider_reset`	provider_reset	Reset the current provider and remove stored credentials
`/queue`	queue	Inspect the message input queue: /queue [list|clear|next|help]
`/quit`	quit	Exit ragent
`/reload`	reload	Reload customizations (/reload [all|config|mcp|skills|agents])
`/resume`	resume	Resume the agent from where it was halted (/resume help)
`/system`	system	Override the agent system prompt (/system | /system help)
`/template`	template	List and apply reusable prompt templates: /template [name] [args]
`/goal`	goal	Goal-based autonomous stop: /goal set|clear|show|test
`/gcf`	gcf	Toggle GCF encoding of tool results: /gcf on|off|show|help

Command	Document	Summary
`/tools`	tools	List every registered tool: /tools (help) | /tools list|show | /tools help
`/skills`	skills	List all registered skills and their descriptions (/skills help)
`/skill`	skill	Load or inspect skill packs: /skill | /skill list | /skill [args] | /skill help
`/mcp`	mcp	MCP servers: /mcp [status] | /mcp discover | /mcp connect | /mcp disconnect | /mcp help
`/task`	task	Toggle the TASKS side panel, or list/help tasks: /task [list|help]
`/team`	team	Team management (/team help|status|show [name]|create/open/delete |close|message |tasks|clear|cleanup)
`/swarm`	swarm	Auto-decompose a goal into parallel subtasks (/swarm | /swarm status | /swarm help)
`/spawn`	spawn	Launch a detached fire-and-forget background sub-agent: /spawn <prompt…> | /spawn help
`/bash`	bash	Manage bash command lists: /bash add|remove allow|deny [–global] | show | help
`/dirs`	dirs	Manage directory/file permission lists: /dirs add|remove allow|deny [–global] | show | help
`/yolo`	yolo	Toggle YOLO mode - bypass all command validation and tool restrictions (/yolo help)
`/security`	../llmsecurity	LLM security analyzer: /security on|off|status|revert|help (tightening-only permission layer)
`/spec`	spec	Specification management: /spec cre-ate|add|delete|list|search|validate|status|task|govcreate|h

Command	Document	Summary
`/plugins`	plugins	Plugin management: /plugins list [–verbose] | add [–force] | remove | enable | disable | test | codex [query] [–category] [–refresh] | claude [query] [–category] [–refresh] | stores [–check] | help
`/connectors`	connectors	Connector management: /connectors list [–verbose] [–category] | claude [query] [–category] [–refresh] | add <id|source> [–force] | remove | enable | disable | connect | disconnect | auth | test | stores [–check] | help
`/research`	research	Research system: /research create [–mode tiered|supervisor|competitive] [–summarization-model] [–evaluate] [other flags] <topic…> | list | open | search | show | delete | archive | cluster
`/spec reverse`	reverse	Reverse-engineer a GitHub repo: /spec reverse <owner/repo | URL> [–language –type [–stack]] [–create] [–depth] [–folder] [–github | –gitlab]
`/new`	new	Scaffold a new project: /new –language –type [–stack] [–github | –gitlab] | /new help
`/autopilot`	autopilot	Autonomous operation: /autopilot on [–max-tokens N] [–max-time N] | off | status | help
`/plan`	plan	Delegate planning to the plan agent: /plan
`/mode`	mode	Set agent role mode: /mode architect|coder|reviewer|debugger|tester|off|help
`/memory`	memory	Memory panel (Alt+M): /memory | /memory show | /memory clear | /memory help
`/github`	github	GitHub integration: /github login | logout | status | help
`/gitlab`	gitlab	GitLab integration: /gitlab setup | logout | status | help
`/update`	update	Check for or install updates: /update | /update install | /update help

Command	Document	Summary
`/doctor`	doctor	Run system diagnostics (providers, git, ripgrep, MCP, memory); /doctor help for details
`/webapi`	webapi	Manage the HTTP REST API: /webapi enable | disable | help
`/websearch`	websearch	Web search engine diagnostics: /websearch show | test | help
`/init`	init	Analyse the project and write a summary, or create a default config: /init [config|help]
`/codeindex`	codeindex	Manage codebase index: /codeindex on|off|show|lang|reindex|rebuild|graph <build|export|lang>|explain |path |communities|godnodes|help
`/status`	status	Show status message history: /status [clear]
`/mouse`	mouse	Toggle mouse support: /mouse on | off | help
`/telemetry`	telemetry	Telemetry management: /telemetry help|on|off|setup|counters
`/telemetry_panel`	telemetry_panel	Toggle the telemetry side panel; use `/telemetry counters` to list values
`/router`	router	Model router management: /router on|off|status|tiers|weights|boundaries|test|stats|reload|he
`/startup`	startup	Show startup timing breakdown for the current session
`/editlog`	editlog	Edit-operation logging: /editlog on|off|status|show|analyse|clear
`/actionloop`	actionloop	Agent action-loop timing: /actionloop [help|clip]
`/bug-report`	bug-report	Generate diagnostic bug report with redacted session data (output to log/)
`/triggers`	triggers	Manage trigger rules: /triggers [list|enable|disable|remove|status|help]
`/undo`	undo	Remove the last user/assistant turn pair from the conversation (/undo help)
`/name`	name	Set a human-readable display name for the session: /name | /name help

Command	Document	Summary
`/alog`	alog	Activity log: /alog help|on|off|config|list|status|delete –yes|export –yes
`/toolchain`	toolchain	Language toolchain report: /toolchain list [lang] [–json] | /toolchain help
`/prompt`	prompt	Agent system-prompt inspector: /prompt help|primary [agent]|subagent [agent]|list|
`/blueprints`	blueprints	List installed team blueprints: /blueprints help|list
`/osinfo`	osinfo	Host OS and hardware report: /osinfo show [–no-probe]|help

Aliases

Alias	Canonical
`/exit`	`/quit` (single dispatch arm `"quit" | "exit"`)
`/teams`	`/team` (single dispatch arm `"team" | "teams"`)
`/compress`	`/compact` (deprecated alias; logs a deprecation notice)