/profile

Toggle the agent-loop profiler panel (/profile on|off|help)

Overview

`/profile` toggles the agent-loop profiler side panel, which reads `AgentLoopProfiler::snapshot()` and displays the recorded action-loop timing samples. The profiler must be enabled before `/actionloop` has data to report.

Syntax

```
/profile            Print the help table (same as /profile help)
/profile on         Enable the profiler panel
/profile off        Disable the profiler panel
/profile help       Print the help table
```

Options / Subcommands

Form	Description
`on`	Enable the profiler panel via `set_profile_panel_enabled(true)`.
`off`	Disable the profiler panel.
`help`	Print the help table, which notes that it reads `AgentLoopProfiler::snapshot()` and that the alias `/perf` behaves identically.

`--help` and `-h` are accepted as aliases of `help`; the bare form also prints help. Any other argument prints the usage text.

Examples

`/profile on`

Opens the profiler side panel and starts collecting action-loop timing data.

`/profile off`

Closes the profiler side panel.

`/profile help`

Prints the help table including the alias note.

```
/profile on
/actionloop
```

Enable profiling, then read the timing report.

Output

`on`/`off` confirm the panel state change. `help` prints the table that cites the profiler snapshot source and mentions the `/perf` alias. Unknown arguments print the usage line.

Related

- `/perf` – full alias of `/profile` with identical semantics.
- `/actionloop` – prints the timing report the profiler records.