

/codeindex

Manage codebase index: /codeindex on|off|show|lang|reindex|rebuild|graph <build|export|lang>|explain
|path |communities|godnodes|help

Overview

/codeindex controls the codebase indexing subsystem: tree-sitter parsing into a SQLite store, Tantivy full-text search, the file watcher, and the semantic code graph (FR-015). Enablement persists to .ragent/ragent.json; the index itself lives under .ragent/codeindex. Most report subcommands are read-only and never trigger a scan; only reindex and rebuild do background work. Graph queries require a graph dataset, which is built on demand with /codeindex graph build.

Syntax

```
/codeindex on | enable
/codeindex off | disable
/codeindex show | status
/codeindex reindex
/codeindex lang | languages
/codeindex rebuild
/codeindex graph build
/codeindex graph lang <language>
/codeindex godnodes [N]
/codeindex explain <symbol>
/codeindex path <symbolA> <symbolB>
/codeindex communities
/codeindex help
```

Notes:

- The bare form is equivalent to /codeindex show.
- /codeindex graph export appears in the help/usage line but is NOT implemented in the dispatcher - there is no export arm. Only build and lang work under graph.
- /codeindex skillgen also exists in the code but is unadvertised; it is not part of the supported surface below.

Options / Subcommands

Form	Description
/codeindex on (alias enable)	Enable the code index, persist the setting, open/create the index at .ragent/codeindex, and start the file watcher (which performs an initial full reindex).
/codeindex off (alias disable)	Stop the watcher and drop the in-memory index and stats cache.
/codeindex show (aliases status, bare)	Print the full status report (see Output). Non-blocking: never waits on the store lock.
/codeindex reindex	Kick a background re-scan of the codebase. Requires an active index.

Form	Description
<code>/codeindex lang (alias languages)</code>	List supported scanner languages, 5 per line, with the total count.
<code>/codeindex rebuild</code>	Rebuild the full-text search index from the SQLite store.
<code>/codeindex graph build</code>	Build the semantic code graph in the background.
<code>/codeindex graph lang <language></code>	Show the graph-related language coverage for the code index.
<code>/codeindex godnodes [N]</code>	Print the N most-connected symbols (default 10, clamped 1-100) as a table.
<code>/codeindex explain <symbol></code>	Print node metadata plus incoming and outgoing graph edges for the symbol.
<code>/codeindex path <A> </code>	Print the shortest symbol-to-symbol path as a hop chain.
<code>/codeindex communities</code>	Run/print community detection over the graph.
<code>/codeindex help</code>	Print the help page.

Examples

Enable indexing and let the watcher perform the initial scan:

```
/codeindex on
```

Check the index, FTS, and graph state:

```
/codeindex show
```

Refresh the index after a bulk import:

```
/codeindex reindex
```

Find which symbols sit at the centre of the dependency web (top 20 instead of the default 10):

```
/codeindex godnodes 20
```

Trace the shortest route from an entry point to a helper:

```
/codeindex path main process_message
```

See how the codebase clusters, and which languages the scanner supports:

```
/codeindex communities
```

```
/codeindex lang
```

Output

on | enable

- [ok] Code index: enabled and activated. Background reindex in progress.
- If the config save fails: [warn] enabled in memory, but saving config failed plus status codeindex: on (unsaved).

off | disable

- When it was active: disabled and deactivated. Codeindex tools will no longer be available. Use `/codeindex on` and restart to re-enable.
- When it was not active: disabled. It was not currently active.

show | status | bare

Prints, per the non-blocking `try_status()` snapshot:

- Enabled, Files indexed, Total symbols, FTS documents, References, Total size KB.
- FTS warnings: when the FTS document count is empty, run `rebuild`; when FTS documents are below 50 percent of the symbol count, the FTS index may be out of sync.
- Languages with per-language symbol counts.
- Last full index and Last incremental timestamps, plus Index size.
- Graph Dataset section: while building, progress as `done/total files`; when edges are 0, not built. Run `/codeindex graph build`; otherwise Total edges, Nodes, edges by confidence (EXTRACTED/INFERRED), Communities, and edges by kind (calls, imports, inherits, references, mixes_in, implements).
- When another task holds the store lock, a busy banner with `reindex` progress (`done/total files`) and/or graph-build progress, plus guidance to retry.

reindex

- Requires an active index; status: `[wait] codeindex: reindexing...`

lang | languages

- Supported language ids, 5 per line, followed by the total count.

rebuild

- `[ok] FTS rebuild complete: N documents indexed.`
- On failure: `[err] FTS rebuild failed`

graph build | graph lang

- `graph build` starts the background graph build (progress surfaces in `show` and in the busy banner).
- The graph usage line mentions `export`, but no export arm is implemented - only `build` and `lang <language>` are accepted.

godnodes [N]

- Table: # | Symbol | Source File | Degree. Default N is 10, clamped to the range 1-100.

explain

- Header with node metadata (source file, line, community, degree) plus two tables, Incoming and Outgoing: Symbol | File | Kind | Confidence.
- Unknown symbol: a `[warn]` not-found message.

path

- Hop chain, each hop rendered as A` --kind--> `B with confidence tags.
- No connecting path: [warn] no-path message.

communities

- Table: Community | Label | Members.
- No communities detected: [warn] No communities detected.

Shared guards

- Graph subcommands without graph data: [warn] No graph data available. Run `/codeindex graph build` first...
- Any subcommand requiring an active index when none is active: [warn] Code index is not active. Enable it first with `/codeindex on`

Related

- Full codeindex manual: `docs/howtos/codeindex.md`.
- `/codeindex on|off` state, language filtering, and the `idx/graph` status bar busy indicators.
- `codeindex_search`, `codeindex_symbols`, `codeindex_references`, `codeindex_dependencies`, `codeindex_explain`, `codeindex_path`, `codeindex_communities`, `codeindex_godnodes` LLM tools.
- `/tools codeindex on|off` controls tool visibility rather than indexing.