

/help

Show available slash commands

Overview

/help prints the full list of slash commands in a fenced code block, one command per line in a fixed-width column, drawn from the SLASH_COMMANDS registry (the same definitions that drive autocomplete). After the built-in commands, it appends a Skills: section listing every user-invokable skill loaded from the configured skill directories, with its argument hint appended to the trigger and its description (or (no description)).

It takes no arguments and performs no filtering - it is always the complete inventory.

Syntax

/help

Options / Subcommands

Form	Description
/help	List all available slash commands plus user-invokable skills

No arguments or subcommands.

Examples

/help

Built-in commands section (fixed-width columns inside a code block):

Available commands:

```
/about      Show application info, version, and authors
/agent      Switch the active agent: /agent [<name>] | /agent help
/agents     List all agents - built-in and custom
...
```

Skills section (appended when any user-invokable skills are loaded):

Skills:

```
/docupdate  Refresh docs and CHANGELOG
/release <args> Run the release pipeline
```

/help

No skills loaded: the output ends after the built-in command block.

Output

- One assistant bubble From: `/help` containing a fenced code block of all registered commands (`{trigger}` padded, then description), optionally followed by a `Skills:` list of user-invokable skills from the skill registry (name + argument hint on the left, description on the right).
- The working directory and skill directories come from the loaded ragent config; skills are discovered fresh at each invocation.
- Status bar shows `help`.

Related

- `/agents` - list agents (commands are listed by `/help`, agents by `/agents`)
- Skills are custom YAML packs in the configured skill directories
- `/help` per-command variants such as `/agent help`, `/cancel help`, `/history help` print their own subcommand tables