# /editlog

Edit-operation logging: /editlog on|off|status|show|analyse|clear

## Overview

`/editlog` manages the edit-operation log, a record of every file-edit tool call (read, write, edit, multiedit, patch, apply_patch, …) and whether it succeeded. Use it to diagnose why edits keep failing: `show` summarises per-tool success rates and `analyse` inspects the failed `old_str` values to characterise why they missed.

## Syntax

```
/editlog            Print the help table (same as /editlog help)
/editlog on         Enable edit-operation logging
/editlog off        Disable edit-operation logging
/editlog status     Show enabled state and log directory
/editlog show       Per-tool statistics table
/editlog analyse    Failed old_str analysis
/editlog clear      Empty the edit-log files (files kept)
/editlog help       Print the help table
```

## Options / Subcommands

| Form | Description |
|---|---|
| `on` | Enable edit-operation logging via `persist_edit_log`. |
| `off` | Disable edit-operation logging. |
| `status` | Show whether logging is enabled and where the log lives (`log/`). |
| `show` | Render a per-tool table: tool name, total calls, successes, failures, success percentage, plus the recorded failure reasons. |
| `analyse` | Characterise the failed `old_str` values (risk traits, per-tool failure ratios, most common failure combinations, sample examples). |
| `clear` | Empty the edit-log files without deleting them; reports the number of cleared entries. |
| `help` | Print the help table. |

`--help` and `-h` are accepted as aliases of `help`.

## Examples

`/editlog on`

Starts recording every edit operation.

`/editlog status`

Confirms logging is enabled and prints the `log/` directory used.

`/editlog show`

Shows a table such as:

```
Tool         Calls  OK  Fail   Pct
edit           142  130   12    92
multiedit       38   33    5    87
```

`/editlog analyse`

Reports the risk characteristics of failed `old_str` blocks: per-tool failure ratios, the most common failing combinations (top 10), and concrete examples.

`/editlog clear`

Empties the log files and prints the cleared-entry count; the files remain so future stats continue to accumulate.

`/editlog help`

Prints the table above.

## Output

`on`/`off` confirm the state change; a failed persist is reported as a `[warn]` line. `status` prints enabled/disabled plus the directory. `show` prints a fixed-width per-tool stats table with success percentages and the failure reasons seen. `analyse` prints a breakdown of failed `old_str` characteristics, per-tool ratios, top combinations, and examples. `clear` prints how many entries were emptied.

## Related

- `/editlog` statistics are cleared by `/log clear editlog`.
- `/log` – log panel and directory clearing.
- `log/editlog/` – where the edit log is written.