# Tools — Teams

Multi-agent coordination inside an active team: named teammates, a shared task list, mailbox messaging, and plan approval. All team tools require an active team, and `team_name` is required by nearly every tool.

| Tool | Description |
|---|---|
| `team_create` | Create a named team from a blueprint. |
| `team_spawn` | Spawn a teammate for a scoped task. |
| `team_message` | Direct message a teammate or lead. |
| `team_broadcast` | Message all active teammates. |
| `team_read_messages` | Check mailbox for unread messages. |
| `team_status` | Team and task status summary. |
| `team_task_list` | List all team tasks. |
| `team_task_create` | Lead adds a shared task. |
| `team_task_claim` | Teammate claims the next available task. |
| `team_task_complete` | Mark a claimed task done. |
| `team_assign_task` | Lead assigns a task to a teammate. |
| `team_submit_plan` | Teammate submits a plan to the lead. |
| `team_approve_plan` | Lead approves/rejects a plan. |
| `team_wait` | Block until teammates finish. |
| `team_idle` | Teammate signals no more work. |
| `team_shutdown_teammate` | Lead requests teammate shutdown. |
| `team_shutdown_ack` | Teammate acks shutdown and exits. |
| `team_cleanup` | Lead tears down the team. |
| `team_memory_read` | Read team memory bucket. |
| `team_memory_write` | Write team memory bucket. |

**Visibility switch:** `teams`. See `docs/howtos/teams.md` for the full team manual and `docs/userdocs/TEAMS.md` for the guide.

---

## team_create

Create a team from a blueprint. Always pass `context` — it is prepended to every teammate's spawn prompt with the specific request details.

**Arguments**

| Argument | Type | Required | Description | Typical value |
|---|---|---|---|---|
| `blueprint` | string | yes | Team template | `"code-review"` |
| `context` | string | yes | Task details: target files, what to do, where to write output | `"Review crates/ragent-server for security issues. Write findings to docs/COMPLIANCE.md"` |

**Workflow:** `team_create` -> `team_wait` (blocks until all teammates idle) -> `team_status` to collect findings.

---

## team_spawn

Add a teammate for one scoped task.

**Arguments**

| Argument | Type | Required | Description | Typical value |
|---|---|---|---|---|
| `team_name` | string | yes | Team name | `"audit-team"` |
| `teammate_name` | string | yes | Unique teammate name | `"reviewer-1"` |
| `agent_type` | string | yes | Agent profile to run | `"coder"` |
| `prompt` | string | yes | Scoped task prompt | — |

---

## team_message

| Argument | Type | Required | Description |
|---|---|---|---|
| `team_name` | string | yes | Team name |
| `to` | string | yes | Recipient teammate name (or lead) |
| `content` | string | yes | Message text |

## team_broadcast

| Argument | Type | Required | Description |
|---|---|---|---|
| `team_name` | string | yes | Team name |
| `content` | string | yes | Message sent to all active teammates |

## team_read_messages

| Argument | Type | Required | Description |
|---|---|---|---|
| `team_name` | string | yes | Team name |

---

### team_status

Team and task status summary.

**Arguments**

| Argument | Type | Required | Description |
|---|---|---|---|
| `team_name` | string | yes | Team name |

---

### team_task_list / team_task_create / team_task_claim / team_task_complete / team_assign_task

| Argument | Type | Required | Applies to | Description |
|---|---|---|---|---|
| `team_name` | string | yes | all | Team name |
| `title` | string | yes | `team_task_create` | Shared task title |
| `task_id` | string | yes | `team_task_complete`, `team_assign_task` | Task identifier |
| `to` | string | yes | `team_assign_task` | Teammate to assign to |

`team_task_claim` takes no extra arguments: the teammate claims the next available task from the shared list. `team_task_complete` takes `team_name` + `task_id` (not `summary`).

---

### team_submit_plan / team_approve_plan

| Argument | Type | Required | Applies to | Description |
|---|---|---|---|---|
| `team_name` | string | yes | both | Team name |
| `plan` | string | yes | `team_submit_plan` | Plan text proposed by a teammate |
| `teammate` | string | yes | `team_approve_plan` | Teammate whose plan is judged |
| `approved` | boolean | yes | `team_approve_plan` | Approve or reject |

---

### team_wait / team_idle / team_shutdown_teammate / team_shutdown_ack / team_cleanup

| Argument | Type | Required | Applies to | Description |
|---|---|---|---|---|
| `team_name` | string | yes (optional for `team_wait`, uses active team) | all | Team name |
| `teammate` | string | yes | `team_shutdown_teammate` | Teammate to shut down |

`team_wait` blocks until spawned teammates finish — always use it after `team_create`/`team_spawn`. `team_cleanup` tears down team state after all teammates have stopped.

---

### team_memory_read / team_memory_write

| Argument | Type | Required | Applies to | Description |
|---|---|---|---|---|
| `team_name` | string | yes | both | Team name |
| `content` | string | yes | `team_memory_write` | Content stored in the shared memory bucket |