

## Tool Visibility

ragent can hide or expose whole tool families through persistent visibility switches. This keeps the model's advertised tool list focused without removing the tools from the binary.

### Switches

The available switches are:

| Switch      | Default | Family                                                                                                     |
|-------------|---------|------------------------------------------------------------------------------------------------------------|
| github      | off     | GitHub issue and PR tools                                                                                  |
| gitlab      | off     | GitLab issue, MR, pipeline, and job tools                                                                  |
| teams       | off     | Team coordination tools                                                                                    |
| agents      | off     | Autonomous agent task tools                                                                                |
| plan        | off     | Plan-mode tools                                                                                            |
| codeindex   | on      | Code index tools                                                                                           |
| masterfetch | on      | MasterFetch web-access tools<br>(mf_fetch, mf_search, mf_crawl, mf_screenshot, mf_cache_clear, mf_version) |
| browser     | on      | Browser automation tool<br>(browser — Chrome DevTools Protocol)                                            |

When a switch is off, tools in that family are excluded from:

1. The tool list advertised in the system prompt
2. The tool schema list sent to the provider

The tools remain registered, but the model is not told to use them. `/tools list` prints Visible Tools (N total, M disabled) and then a Disabled by visibility (M) section listing every hidden-but-still-registered tool (it is the complement of the model-facing tool list, backed by `ToolRegistry::hidden_definitions()`), so a family switched off stays visible in the report instead of vanishing.

### Slash commands

Use these from the TUI (`/tools` on its own prints the help):

```
/tools
/tools list
/tools help
/tools <switch>
/tools <switch> on
/tools <switch> off
```

`/tools list` (alias `/tools show`) renders the family visibility table plus every visible and disabled tool.

Examples:

```
/tools github on
/tools teams on
/tools teams off
/tools agents off
/tools plan off
/tools codeindex off
/tools masterfetch off
/tools browser off
```

Changes are written to `.ragent/ragent.json` when a project config directory is present, or to the user config otherwise.

## Config file

You can also configure visibility directly in `ragent.json`:

```
{
  "tool_visibility": {
    "github": false,
    "gitlab": false,
    "teams": false,
    "agents": false,
    "plan": false,
    "codeindex": true,
    "masterfetch": true,
    "browser": true
  }
}
```

## Interaction with hidden\_tools

`hidden_tools` is still supported. It remains additive:

- `tool_visibility` hides whole families
- `hidden_tools` hides specific tool names

If either mechanism hides a tool, that tool stays out of the advertised tool set.

## Code index compatibility

`/codeindex on` and `/codeindex off` also keep `tool_visibility.codeindex` in sync, so the code index command and the tool visibility command do not drift.