

/tools

Toggle tool visibility: `/tools [github|gitlab|teams|agents|plan|codeindex|masterfetch|browser]`
`[on|off] | /tools help`

Overview

`/tools` has two behaviours. The bare form (and `/tools show`) prints the tool visibility table - the current on/off state of every visibility switch. With a switch name it reports that switch's state, and with a switch plus a state word it toggles the visibility of that tool family for the session and saves the choice to the active config source.

Note the registry description lists seven switches but the implementation accepts eight: `github`, `gitlab`, `teams`, `agents`, `plan`, `codeindex`, `masterfetch`, and `browser`. Toggling a switch rewrites `tool_visibility` in the config source and invalidates the session processor's config cache so the change takes effect immediately.

Syntax

```
/tools                # show the visibility table (same as: show)
/tools show           # same as bare form
/tools <switch>       # read one switch's state
/tools <switch> on|off # set one switch (enable/disable also accepted)
/tools help           # usage help (aliases: --help, -h, usage)
```

Options / Subcommands

Form	Description
<code>/tools</code>	Render the tool visibility table
<code>/tools show</code>	Same as the bare form
<code>/tools <switch></code>	Report whether <switch> is currently on or off
<code>/tools <switch> on</code>	Enable the switch (enable also accepted)
<code>/tools <switch> off</code>	Disable the switch (disable also accepted)
<code>/tools help</code>	Print usage help

Switches (all eight accepted): `github`, `gitlab`, `teams`, `agents`, `plan`, `codeindex`, `masterfetch`, `browser`.

Examples

Show the visibility table:

```
/tools
```

Read a single switch:

```
/tools teams
```

Turn the GitHub tool family off for this project:

```
/tools github off
```

Re-enable codeindex tools:

```
/tools codeindex on
```

Disable the browser tool family:

```
/tools browser disable
```

Print the usage help:

```
/tools help
```

Output

Visibility table (bare form): one row per switch with its on/off state.

Single switch read:

```
`teams` is currently **on**.
```

Successful toggle (the config is saved and the config cache invalidated):

```
[ok] `` visibility is now **on**.
```

Invalid state word:

```
[warn] Usage: /tools <switch> on|off
```

Config save failure (the in-session change still applied):

```
[warn] `` visibility changed ... but saving config failed: <error>
```

and the status bar notes tools: <switch> ... (unsaved).

Related

- `/config show` - inspect the resolved configuration including tool visibility
- `/reload config` - re-read `ragent.json` after manual edits
- `tool_visibility` section in `ragent.json` - persistent equivalent of these switches