

/triggers

Manage trigger rules: `/triggers [list|enable|disable|remove|status|help]`

Overview

`/triggers` manages trigger rules: conditions that fire an action automatically (for example, running a command when a file appears). Rules are not created by this command – they are created by natural language elsewhere (e.g. “when \$HOME/build.done exists, run cargo test”) – so `/triggers` lists, toggles, removes, and reports metrics for the existing rule set.

Syntax

<code>/triggers</code>	List trigger rules (same as <code>/triggers list</code>)
<code>/triggers list</code>	List trigger rules
<code>/triggers enable <rule_id></code>	Enable a rule
<code>/triggers disable <rule_id></code>	Disable a rule
<code>/triggers remove <rule_id></code>	Remove a rule
<code>/triggers status</code>	Show runtime metrics
<code>/triggers help</code>	Print the usage table

Options / Subcommands

Form	Description
list (or bare)	Print a table of rules: ID (8-character prefix), condition, action, mode (once or repeat), and status (active, disabled, or fired). With no rules defined, prints the empty-state message explaining that rules are created by natural language.
enable <rule_id>	Enable the rule with the given ID prefix.
disable <rule_id>	Disable the rule so it no longer fires.
remove <rule_id>	Delete the rule.
status	Print runtime metrics: total/active/disabled/fired counts, dedup cache entries, cycle trackers, dedup window seconds, and max cycles.
help	Print the usage table.

Unknown subcommands print a warning.

Examples

```
/triggers list
```

Shows the rule table (ID, condition, action, mode, status) or the empty-state explainer if none exist yet.

```
/triggers enable 3f9a2c
```

Re-enables the rule whose ID prefix is 3f9a2c.

```
/triggers disable 3f9a2c
```

Stops the rule from firing without deleting it.

```
/triggers remove 3f9a2c
```

Deletes the rule.

```
/triggers status
```

Prints the metrics table: total, active, disabled, fired, dedup cache entries, cycle trackers, dedup window secs, max cycles.

```
/triggers help
```

Prints the usage table.

Output

`list` prints the fixed-width rule table, or the empty-state note that rules are created by natural language. `enable/disable/remove` confirm the change for the given ID prefix. `status` prints the runtime metrics table. `help` prints the usage table; unknown subcommands print a warning line.

Related

- Natural-language rule creation (rules are made by asking the agent, not by a slash-command form).
- `/status` – unrelated; shows status-message history.