

/webapi

Control the built-in HTTP API server (/webapi status|enable|disable)

Overview

/webapi manages the axum-based HTTP server that lets any frontend drive the agent over REST and SSE. With no arguments (or status, help, -h, --help) it prints the help text, the current server state, and a table of the available endpoints. enable starts the server and generates a fresh bearer token; disable stops it.

Syntax

/webapi	Show help, status, and the endpoint table
/webapi status	Same output as the bare form
/webapi help	Same output as the bare form
/webapi -h	Same output as the bare form
/webapi --help	Same output as the bare form
/webapi enable	Start the HTTP server and generate a bearer token
/webapi start	Alias of enable
/webapi disable	Stop the HTTP server
/webapi stop	Alias of disable

Options / Subcommands

Form	Description
/webapi	Renders the help text, current state, and endpoint table
/webapi status	Alias of the bare form
/webapi help	Alias of the bare form
/webapi -h / --help	Aliases of the bare form
/webapi enable	Starts the server and generates a 40-character alphanumeric bearer token, printing curl usage examples
/webapi start	Alias of enable
/webapi disable	Stops the running server
/webapi stop	Alias of disable

Authentication

- GET /health requires no authentication and can be used as a liveness probe.
- Every other endpoint requires the header `Authorization: Bearer <token>` where <token> is the 40-character alphanumeric token generated by /webapi enable.
- A new token is generated on each enable; enabling again replaces the previous token.

Examples

```
/webapi
```

Prints the help text, the running/stopped status, and the endpoint table.

`/webapi enable`

Starts the HTTP server and prints the generated bearer token together with ready-to-copy curl examples.

`/webapi start`

Identical to `enable`.

`curl http://127.0.0.1:9100/health`

Liveness check; no `Authorization` header needed.

`curl -H "Authorization: Bearer <token>" http://127.0.0.1:9100/sessions`

Authenticated request against a protected endpoint.

`/webapi disable`

Stops the HTTP server.

Output

- Bare `/` `/status` `/help` forms: the help block, the current state (running or stopped, with the listen port), and a table of the REST and SSE endpoints.
- `enable`: confirmation that the server started, the generated 40-character bearer token, and curl examples showing how to call the API.
- `disable`: confirmation that the server stopped.
- Unknown subcommand: a warning message.

Related

- `/websearch` - inspect and diagnose the web search engine configuration
- `ragent serve --port 9100` - run the HTTP server without the TUI
- SSE streaming and REST routes are implemented in the `ragent-server` crate