

Tools — Memory

Three-tier memory: structured SQLite store (these tools), file blocks, and optional embedding-based semantic search. Structured memories carry a category, tags, and a confidence score.

Tool	Description
<code>memory_store</code>	Store a structured memory (category, tags, confidence).
<code>memory_recall</code>	Full-text search of structured memories.
<code>memory_forget</code>	Delete memories by ID or filter.
<code>conversation_search</code>	Search current session conversation history.
<code>session_search</code>	Search across all past sessions.

Confidence scale: 0.0 = uncertain, 1.0 = certain. Use 0.7 for ordinary observations, ≥ 0.9 for verified facts, ≤ 0.5 for hunches. Tags are free-form but should be lowercase and hyphenated (e.g. `rust`, `startup`).

`memory_store`

Store a structured memory.

Arguments

Argument	Type	Required	Description	Typical value
<code>content</code>	string	yes	The memory content — a fact, pattern, insight, etc.	"We use anyhow::Result for errors"
<code>category</code>	enum	yes	fact, pattern, preference, insight, error, workflow	"preference"
<code>tags</code>	array	no	Lowercase/hyphenated strings for filtering	["rust", "error-handling"]
<code>confidence</code>	number	no	0.0–1.0 (default 0.7)	0.9
<code>source</code>	string	no	Source of the memory	"manual", "auto-extract"

Example:

```
memory_store content="We use anyhow::Result for errors" category="preference" confidence=0.9
memory_recall query="error handling"
```

`memory_recall`

Full-text search of structured memories. All keyword terms must match (AND); broaden by removing terms. Access counts are incremented on return.

Arguments

Argument	Type	Required	Description	Typical value
query	string	yes	Space-separated search terms	"error handling"
categories	array	no	Restrict to these categories	["pattern", "workflow"]
tags	array	no	Memories must have ALL these tags	["rust"]
limit	integer	no	Maximum results	5
min_confidence	number	no	Confidence threshold	0.5
			0.0–1.0	

memory_forget

Delete memories by ID or by filter criteria. At least one criterion is required as a safety measure.

Arguments

Argument	Type	Required	Description
id	integer	one criterion	Delete one memory by its row ID
older_than_days	integer	one criterion	Delete memories not updated in this many days
max_confidence	number	one criterion	Delete memories with confidence at or below this value
category	enum	one criterion	Delete all memories in the category
tags	array	one criterion	Delete memories that have ALL of these tags

Example: `memory_forget max_confidence=0.2`

conversation_search

Search the current session conversation history. Modes: `keyword` (default), `turn_range`, `stats`.

Arguments

Argument	Type	Required	Description	Typical value
query	string	yes for keyword	Search query	"cargo fmt"

Argument	Type	Required	Description	Typical value
mode	enum	no	keyword (default), turn_range, stats	"keyword"
start_turn / end_turn	integer	yes for turn_range	1-based inclusive turn range	1 / 20
limit	integer	no	Keyword match count	10
context_turns	integer	no	Surrounding turns per keyword match	0

Example: `conversation_search query="edit old_string" limit=5`

session_search

Search across all past sessions using FTS5 keyword search.

Arguments

Argument	Type	Required	Description	Typical value
query	string	yes	FTS5 keyword search (implicit AND across terms)	"compaction runner"
since / until	string	no	ISO-8601 date range bounds	"2026-09-01"
working_dir	string	no	Restrict to sessions in this directory	—
roles	array	no	Restrict to these roles	["user", "assistant"]
session_id	string	no	Restrict to a single session id	—
limit	integer	no	Maximum total results	10
max_per_session	integer	no	Cap results from any one session	3
include_tools	boolean	no	Include tool-call content (default true)	false
include_system	boolean	no	Include system/compaction messages	false
context_turns	integer	no	Surrounding turns included per result	0

Example:

`session_search query="govdoc spec" since="2026-09-01" limit=10`