

Tools — Web

Simple HTTP fetching and web search. For rich HTML-to-markdown extraction, PDFs, bulk fetches, or envelope signals (`content_ok`, `is_official`, `is_stale`), prefer the MasterFetch tools.

Tool	Description
<code>webfetch</code>	Fetch a URL via HTTP GET; HTML converted to text.
<code>websearch</code>	Web search returning titles, URLs, snippets.
<code>http_request</code>	Full HTTP method/headers/body control.

Use cases: fetching documentation pages, testing APIs, quick scraping.

webfetch

Fetch the content of a URL via HTTP GET. HTML is converted to plain text unless `format: "raw"` is requested.

Arguments

Argument	Type	Required	Description	Typical value
<code>url</code>	string	yes	URL to fetch (HTTP/HTTPS only)	"https://rust-lang.org"
<code>format</code>	enum	no	text (HTML → text, default) or raw (unchanged)	"text"
<code>max_length</code>	integer	no	Maximum characters returned	50000
<code>timeout</code>	integer	no	Request timeout in seconds	30

Example:

```
webfetch url="https://rust-lang.org"
webfetch url="https://example.com/page.html" format="raw" max_length=10000
```

websearch

Search the web and return results with titles, URLs, and snippets. Uses the masterfetch multi-engine pipeline by default (keyless backends; optional Tavily/LangSearch keys improve quality).

Arguments

Argument	Type	Required	Description	Typical value
query	string	yes	Search query	"rust async patterns"
num_results	integer	no	Number of results (default 5, max 20)	10

Example:

```
websearch query="tokio spawn_blocking" num_results=10
```

http_request

Perform an HTTP request with full control over method, headers, and body. Returns the status code, selected headers, and the body (truncated at 1 MiB).

Arguments

Argument	Type	Required	Description	Typical value
url	string	yes	Full URL including scheme	"https://api.github.com/repos/rust-lang/rust"
method	enum	no	GET (default), POST, PUT, PATCH, DELETE, HEAD, OPTIONS	"GET"
headers	object	no	Request headers as key/value map	{"Authorization": "Bearer ..."}"
body	string	no	Request body (for POST/PUT/PATCH)	"{"name": "x"}"
timeout	integer	no	Timeout in seconds	30

Example:

```
http_request url="https://api.github.com/repos/rust-lang/rust" method="GET"
http_request url="https://httpbin.org/post" method="POST" body="{\"a\":1}"
```