/bench

Benchmark runner: /bench list|init |show|run |status|open last|cancel

Overview

The `/bench` command drives the ragent benchmark harness (`ragent-bench` crate). It initialises benchmark suites, runs them against configured LLM models, and inspects results. The TUI arm parses its arguments with `ragent_bench::parse_bench_command` and dispatches the parsed command to the bench runtime; everything below the `/bench` prefix is handled by the bench crate, not the TUI itself.

Suites measure tool-calling behaviour, code quality, and end-to-end agent runs. Results are stored under the bench output directory so later `run` invocations can resume or compare against previous releases.

Syntax

```
/bench list
/bench init <suite-or-all-or-full> [--full] [--language LANG] [--force-download] [--verify-only]
/bench show <suite>
/bench run <suite-or-profile-or-all> [flags]
/bench status
/bench open last
/bench cancel
/bench help
```

Options / Subcommands

Form	Description
`list`	List the registered benchmark suites and profiles
`init <suite-or-all-or-full>`	Initialise fixtures for a suite, all suites, or the full corpus
`init ... --full`	Build the complete (large) fixture set instead of the default sample
`init ... --language LANG`	Restrict fixture generation to one language
`init ... --force-download`	Re-download fixture inputs even if already cached
`init ... --verify-only`	Verify existing fixtures without generating or downloading
`run <suite-or-profile-or-all>`	Execute a suite, a named profile, or every suite
`run ... --limit N` / `--cap N`	Cap the number of benchmark cases executed
`run ... --samples K`	Number of samples per case
`run ... --subset NAME`	Run only the named subset
`run ... --release VERSION`	Tag the run against a release version
`run ... --scenario NAME`	Run one scenario
`run ... --language LANG`	Restrict the run to one language
`run ... --temperature F`	Override sampling temperature
`run ... --top-p F`	Override top-p sampling

Form	Description
`run ... --max-tokens N`	Override the completion token budget
`run ... --deterministic`	Force deterministic sampling settings
`run ... --since YYYY-MM-DD`	Only include data on or after this date
`run ... --until YYYY-MM-DD`	Only include data on or before this date
`run ... --resume`	Resume a previously interrupted run
`run ... --no-exec`	Parse and plan the run without executing tool calls
`run ... --yes`	Auto-approve prompts during the run
`status`	Show whether a bench run is active and its last known state
`open last`	Open the most recent bench result report
`cancel`	Request cancellation of the active benchmark run
`help`	Print the bench usage help

Examples

```
From: /bench list
Lists every benchmark suite with a short description and case count.
```

```
From: /bench init all
Initialises fixtures for every suite. Progress lines report each suite as it
is generated; use --verify-only afterwards to re-check them.
```

```
From: /bench run codebench --language rust --limit 10
Runs ten rust cases from the codebench suite with the current provider and
model.
```

```
From: /bench run all --deterministic --max-tokens 2048 --release 1.0.95
Runs every suite with deterministic sampling, a 2048-token cap, and stores
the result under release 1.0.95 for later comparison.
```

```
From: /bench status
Reports the state of any in-flight run; prints the last run summary when idle.
```

```
From: /bench cancel
Cancellation requested for the active benchmark run.
```

When no run is active, `cancel` prints “No active benchmark run.” instead.

Output

`init` and `run` stream progress into the message window as the harness works: suite names, case indices, pass/fail outcomes, and aggregate scores. `status` prints the run state; `open last` shows the stored result report; `cancel` prints a confirmation line and the status bar shows `[wait] bench: cancellation requested` while the flag is set.

Related

- `/model` - verify the provider and model a bench run will target
- `/telemetry` - runtime metric counters recorded during runs

- `cargo bench -p ragent-tui` and friends for criterion micro-benchmarks