/name

> "Set a human-readable display name for the session: /name | /name help" (SlashCommandDef, crates/ragent-tui/src/app/state.rs).

Overview

`/name` assigns a display name to the active session (FR-015). The name is persisted in session metadata through the storage layer, so it appears in session lists and survives restarts and resume operations. Calling `/name` with no argument clears the existing name. Use it to label long-running work sessions so they are easy to find later with the `ragent session list` CLI command.

The handler is the `name` arm in `crates/ragent-tui/src/app/slash.rs` (lines 5855-5913).

Syntax

```
/name <display-name>
/name
/name help
```

Options / Subcommands

Form	Description
`/name <display-name>`	Set a human-readable name for the active session (persists in session metadata)
`/name`	Clear the session name
`/name help`	Show the help table

Examples

Name the session

```
/name compaction-benchmarks
```

Status line:

```
Session name set to 'compaction-benchmarks'
```

Log entry: `Session name set to 'compaction-benchmarks'`.

Clear the session name

```
/name
```

Status line:

```
Session name cleared
```

Log entry: `Session name cleared`.

Show help

```
/name help
```

Output:

```
From: /name help

## /name - Session display name

| Subcommand | Description |
|---|---|
| `/name <display-name>` | Set a human-readable name for the active session (persists in session
| `/name` | Clear the session name |
| `/name help` | Show this help |
```

Storage failure

If the underlying storage update fails, the status line shows `[warn] Failed to set session name: <error>` (or `[warn] Failed to clear session name: <error>`) and the log records the error.

Output

- Success (`name set`): status `Session name set to '<name>'` plus an Info log entry.
- Success (`name cleared`): status `Session name cleared` plus an Info log entry.
- No active session: status `[warn] No active session to name`.
- Storage error: `[warn] Failed to set/clear session name: <error>` plus an Error log entry with the same text.

The name is written through `storage.update_session(&session_id, name)`; an empty name argument is the clear path and passes an empty string.

Related

- `ragent session list` (CLI) - see named sessions in the list
- `ragent session resume <id>` (CLI) - resume a named session by id
- `/quit` - leave the session (the name persists for next time)