Tools — Scheduling

Scheduled agent runs (cron events): one-shot or recurring prompts executed by a named agent. New events are enabled by default.

Tool	Description
`cron_add`	Create a scheduled agent run.
`cron_remove`	Delete a scheduled event.
`cron_list`	List all scheduled events.
`cron_enable`	Enable a scheduled event.
`cron_disable`	Disable a scheduled event.

---

cron_add

Create a cron event.

Schedule grammar:

- `at <timestamp>` — one-shot
- `from <timestamp> every <duration>` — repeating from a start time
- `every <duration>` — repeating from now

Timestamps accept ISO-8601 (`2025-01-15T09:00:00Z`) or natural language (`"5pm"`, `"5am tomorrow"`). Durations use `<int><unit>` where unit is `m`, `h`, `d`, `w`, or `mo`.

Arguments

Argument	Type	Required	Description	Typical value
`id`	string	yes	Unique event name (primary key; duplicates fail)	`"daily-audit"`
`agent`	string	yes	Agent type to run	`"general"`, `"coder"`
`schedule`	string	yes	Schedule expression per grammar above	`"every 1h"`
`prompt`	string	yes	Prompt executed when the event fires	`"Run cargo clippy and report new warnings"`

Example:

```
cron_add id="nightly-test" agent="general" schedule="every 1d" prompt="Run cargo test and summari
```

---

cron_remove / cron_enable / cron_disable

Delete an event permanently, or toggle whether the scheduler fires it.

Arguments

Argument	Type	Required	Description
`id`	string	yes	Event identifier

---

cron_list

List all cron events with id, agent, schedule, enabled status, next-due timestamp, and prompt preview. No arguments required.

Example:

```
cron_list
cron_disable id="nightly-test"
```