/team

Team management (/team help|status|show [name]|create/delete |close|message |tasks|clear|cleanup)

Overview

`/team` drives multi-agent team coordination from the TUI: create a team from a blueprint, check team and task status, send mailbox messages to teammates, inspect the shared task list, and tear the team down when finished. Teammates themselves are spawned and coordinated with the `team_*` tools; the `/team` commands manage the surrounding lifecycle.

`/teams` is an alias of `/team`: both triggers dispatch to the same handler and accept the same forms (for example `/teams show <name>`). There is no separate `/teams` command surface.

Syntax

```
/team
/team help
/team status
/team show [name]
/team create <blueprint> [name]
/team close
/team delete <name>
/team blueprint [name]
/team message <teammate-name> <text>
/team tasks
/team clear
/team cleanup
/team forcecleanup [confirm]
/team approve <teammate-name>
/team reject <teammate-name> <feedback>
/team focus [name]
```

Options / Subcommands

Form	Description
`/team` (bare)	Shows the current team status (equivalent to `/team status`).
`help`	Prints the help table.
`status`	Team and task status summary for the active team.
`show [name]`	Shows team details; an optional team name may be given.
`create <blueprint> [name]`	Creates a team from a blueprint. Without `[name]` the team is auto-named `<blueprint>-<YYYYMMDD-HH-MM-SS>` using the current UTC time.
`close`	Closes the active team.
`delete <name>`	Deletes the named team's state.
`blueprint [name]`	Shows or selects the team blueprint.
`message <teammate-name> <text>`	Sends a mailbox message to the named teammate.

Form	Description
`tasks`	Lists the shared team task list.
`clear`	Clears team state.
`cleanup`	Tears the team down after teammates have stopped.
`forcecleanup [confirm]`	Alias `force-cleanup`. Force-cleans the active team: shuts down active teammates and removes the team's on-disk state. Without `confirm` it lists active teammates and asks for Enter (confirm) or Esc (cancel). See teams.md.
`approve <teammate-name>`	Approves the plan of a teammate in `plan_pending` (matched by name or agent id); the teammate begins implementation. See teams.md.
`reject <teammate-name> <feedback>`	Rejects a `plan_pending` teammate's plan with the required feedback; the teammate stays in `plan_pending` and must resubmit with `team_submit_plan`.
`focus [name]`	Focuses the named team; with no argument, clears the current focus.

Examples

```
/team
```

```
/team create code-review
```

```
/team create code-review review-2026-09
```

```
/team message reviewer Please start with the highest-priority task
```

```
/team tasks
```

```
/team cleanup
```

Output

- Bare `/team` and `/team status` print the team and task status summary.
- `/team create` reports the created team; with no name supplied the generated name is `<blueprint>-<YYYYMMDD-HH-MM-SS>` (UTC timestamp).
- `/team message` delivers the text to the named teammate's mailbox.
- `/team tasks` lists the shared task list; claim and complete individual tasks with the `team_task_claim` / `team_task_complete` tools.
- `/team focus` switches which team subsequent team commands address, or clears the focus when called without an argument.

Workflow

A typical team session:

```
/team create <blueprint> [name]     # start the team
/team tasks                         # inspect the shared task list
/team message <teammate> <text>     # coordinate with a teammate
/team cleanup                       # tear down when finished
```

Teammates are added with the `team_spawn` tool and report back through the same task and messaging tools the lead uses.

Related

- `/blueprints` – list installed team blueprints
- `/swarm` – auto-decompose a goal into parallel subtasks
- `team_*` tools – spawn, task, and messaging tools used inside a team
- docs/howtos/teams.md – teams how-to manual