Tools — Interactive

Ask the user questions, record reasoning notes, evaluate expressions, and read environment variables.

Tool	Description
`AskUserQuestion`	Ask the user a question (with optional choices).
`think`	Record a short reasoning note.
`calculator`	Evaluate a mathematical expression.
`get_env`	Read environment variable values.

AskUserQuestion

Ask the user a question and wait for the typed response. With `options` the user picks from a multiple-choice dialog; otherwise they type free text.

Arguments

Argument	Type	Required	Description	Typical value
`question`	string	yes	The prompt shown to the user	`"Which build profile?"`
`options`	array	no	Fixed choices; the returned value will be one of these strings	`["Debug","Release","Check only"]`
`default`	string	no	Option pre-selected in the dialog and used if the question times out; must match one of `options`. When absent, an option marked "recommended" is used, otherwise the first option	`"Debug"`

Example:

```
AskUserQuestion question="Which build profile?" options=["Debug","Release","Check only"]
```

---

think

Record a short reasoning note in the session log without changing project state (published as a reasoning event). Keep entries brief and focused on the next action.

Arguments

Argument	Type	Required	Description
`thought`	string	yes	Short reasoning note

Example: `think thought="Retrying the edit with the verbatim needle from line 42."`

---

calculator

Evaluate a mathematical expression (Python arithmetic + the `math` module; integer/float/complex). Runs in a short-lived `python3` process with a 10-second timeout.

Arguments

Argument	Type	Required	Description	Typical value
`expression`	string	yes	Python-syntax expression	`"math.factorial(20)"`, `"2 ** 32"`

Example: `calculator expression="math.sqrt(2 * math.pi)"`

---

get_env

Read one or more environment variables. Names containing `KEY`, `SECRET`, `TOKEN`, `PASSWORD` (or similar) are redacted to avoid leaking credentials.

Arguments

Argument	Type	Required	Description
`name`	string	one of two	Single variable name
`names`	array	one of two	List of variable names

Example: `get_env name="HOME"`