Tools — PDF

Read and write PDF documents.

Tool	Description
`pdf_read`	Extract text or metadata from a PDF.
`pdf_write`	Write a PDF document.

Visibility switch: none — the PDF family is registered and visible by default. See `docs/howtos/office.md` for the full manual.

---

pdf_read

Extract text, metadata, or structured per-page JSON from a PDF.

Arguments

Argument	Type	Required	Description	Typical value
`path`	string	yes	PDF path	`"spec.pdf"`
`start_page`	integer	no	First page (1-based, inclusive)	`1`
`end_page`	integer	no	Last page (1-based, inclusive)	`10`
`format`	string	no	`text` (default), `metadata`, or `json`	`"metadata"`

Example:

```
pdf_read path="spec.pdf"
pdf_read path="paper.pdf" start_page=3 end_page=7
pdf_read path="report.pdf" format="metadata"
```

---

pdf_write

Write a PDF document from structured content.

Arguments

Argument	Type	Required	Description	Typical value
`path`	string	yes	Output path	`"notes.pdf"`

Argument	Type	Required	Description	Typical value
`content`	object	yes	Document content: optional `title` and an `elements` array of `paragraph`/`heading`/`table`/`image` items	—

Each `content.elements` item:

Field	Type	Required	Description
`type`	enum	yes	`paragraph`, `heading`, `table`, `image`
`text`	string	no	Text content (`paragraph`, `heading`)
`level`	integer	no	Heading level 1-3 (`heading`, default 1)
`headers`	array	no	Column headers (`table`)
`rows`	array	no	Rows, each an array of cell strings (`table`)
`image_path`	string	no	PNG or JPEG file (`image`)
`width_mm`	number	no	Display width in mm (`image`, default: fit page width)
`caption`	string	no	Caption below the image (`image`)

Example:

```
pdf_write path="report.pdf" content={"title":"Report","elements":[{"type":"heading","level":1,"te
```