/tools

Toggle tool visibility: /tools [github|gitlab|teams|agents|plan|codeindex|masterfetch] [on|off] | /tools help

Overview

`/tools` has two behaviours. The bare form (and `/tools show`) prints the tool visibility table - the current on/off state of every visibility switch. With a switch name it reports that switch's state, and with a switch plus a state word it toggles the visibility of that tool family for the session and saves the choice to the active config source.

The implementation accepts seven switches: `github`, `gitlab`, `teams`, `agents`, `plan`, `codeindex` and `masterfetch`. Toggling a switch rewrites `tool_visibility` in the config source and invalidates the session processor's config cache so the change takes effect immediately.

Syntax

```
/tools                          # show the visibility table (same as: show)
/tools show                     # same as bare form
/tools <switch>                 # read one switch's state
/tools <switch> on|off          # set one switch (enable/disable also accepted)
/tools help                     # usage help (aliases: --help, -h, usage)
```

Options / Subcommands

Form	Description
`/tools`	Render the tool visibility table
`/tools show`	Same as the bare form
`/tools <switch>`	Report whether `<switch>` is currently on or off
`/tools <switch> on`	Enable the switch (`enable` also accepted)
`/tools <switch> off`	Disable the switch (`disable` also accepted)
`/tools help`	Print usage help

Switches (all seven accepted): `github`, `gitlab`, `teams`, `agents`, `plan`, `codeindex`, `masterfetch`.

Examples

Show the visibility table:

```
/tools
```

Read a single switch:

```
/tools teams
```

Turn the GitHub tool family off for this project:

```
/tools github off
```

Re-enable codeindex tools:

`/tools codeindex on`

Disable the masterfetch tool family:

`/tools masterfetch off`

Print the usage help:

`/tools help`

Output

Visibility table (bare form): one row per switch with its on/off state.

Single switch read:

`` `teams` is currently **on**. ``

Successful toggle (the config is saved and the config cache invalidated):

`` [ok] `<switch>` visibility is now **on**. ``

Invalid state word:

`[warn] Usage: /tools <switch> on|off`

Config save failure (the in-session change still applied):

`` [warn] `<switch>` visibility changed ... but saving config failed: <error> ``

and the status bar notes `tools: <switch> ... (unsaved)`.

Related

- `/config show` - inspect the resolved configuration including tool visibility
- `/reload config` - re-read `ragent.json` after manual edits
- `tool_visibility` section in `ragent.json` - persistent equivalent of these switches