

/config

“Inspect, back up, and restore ragent configuration” (SlashCommandDef, crates/ragent-tui/src/app/state.rs).

Overview

/config is the in-TUI configuration inspector and backup manager. The `show` form renders the resolved configuration without launching the agent: where the application stores its files, which config files were found on disk, and the final merged value of every key together with the source that supplied it. The `save` form writes a timestamped backup of the global configuration into the `config_dir/saves/` directory, and the `list` form opens an interactive picker over previously saved backups so one can be restored.

Handlers live in `crates/ragent-tui/src/app/slash.rs` (the `config` arm, approximately lines 2238-2652). All output accumulates under a `From: /config` header in the message window.

Syntax

```
/config show
/config save
/config list
/config help
```

Bare `/config` behaves like the `unknown-args` case and prints the usage line.

Options / Subcommands

Form	Description
<code>/config show</code>	Render application paths, discovered config files, and the fully resolved configuration table
<code>/config save</code>	Back up the global config to a timestamped file under <code>config_dir/saves/</code>
<code>/config list</code>	List saved configuration backups and open the restore picker
<code>/config help</code>	Show the subcommand summary

Examples

Inspect resolved configuration

```
/config show
```

Output (representative, condensed):

From: /config show

Application Paths

```
Working directory: /home/user/Projects/ragent
Data directory:   ~/.local/share/ragent
Config directory: ~/.config/ragent
```

Config Files

Path	Exists
/home/user/Projects/ragent/.ragent/ragent.json	yes
/home/user/.config/ragent/ragent.json	no
\$RAGENT_CONFIG	(unset)

Resolved Values

key	source	value
...		

Back up the global configuration

/config save

Output:

From: /config save

[ok] Configuration backed up to /home/user/.config/ragent/saves/ragent.json.20260911-101500

If the backup cannot be written the command reports [err] with No changes were made. and leaves the configuration untouched.

List and restore a saved configuration

/config list

Output (picker state):

From: /config list

Saved configurations (newest first):

1. ragent.json.20260911-101500
2. ragent.json.20260910-183022

...

With no saved backups present the output is:

From: /config list

No saved configurations found

Hint: use /config save to create a backup

Show the subcommand summary

/config help

Output:

From: /config help

/config show | /config save | /config list | /config help

Output

/config show sections

- **Application Paths** - working directory, data directory, and config directory currently in use.

- **Config Files** - a table with exists checks for the project config (<cwd>/`.ragent/ragent.json`), the global config (<config_dir>/`ragent.json`), and the path given by the `RAGENT_CONFIG` environment variable.
- **Resolved Values** - a key | source | value table. Precedence is: defaults < global config < project config < env file < `RAGENT_CONFIG_CONTENT`. Every row names the source that supplied the winning value.
- **Union fields** - the merged-map fields permission, instructions, skill_dirs, hooks, bash, hidden_tools, yolo, edit_log, sdd, piegap, and experimental are labelled global + project (union) when a value is set in both layers.
- **Secret redaction** - keys matching `*_api_key` / `*_key`, plus the `openalex_email`, `gitlab`, `gmail`, and `channels` sections, are redacted before display.
- **Storage** - the resolved SQLite database path.
- **Code Index** - the index directory `.ragent/codeindex`.
- **Memory** - project and global memory directories.
- **Custom Agents** - the custom agent directories being scanned.

`/config save`

Emits `[ok]` with the backup path, or `[err]` with `No changes were made.` when the backup could not be written.

`/config list`

Scans <config_dir>/`saves/` for files matching `ragent.json.*` (excluding `.tmp` candidates), sorts newest-first by modification time, and opens the `ConfigSavePickerState` interactive picker. In the picker:

- Up / Down or `k` / `j` move the selection,
- Enter restores the selected snapshot,
- Esc cancels.

An empty directory produces `No saved configurations found` plus the `/config save` hint.

Unknown arguments

Prints the usage line `/config show | /config save | /config list | /config help`.

Related

- `/init config` - write a fresh default config file to disk
- `/reload` - re-read `ragent.json` into the running session
- `/skills` - view the skill registry loaded from `skill_dirs`
- `QUICKSTART.md` - configuration examples
- `SPEC.md` - full configuration schema