

/github

GitHub integration: /github login | logout | status | help

Overview

/github manages GitHub authentication for the TUI session.

Token sources:

- The GITHUB_TOKEN environment variable
- The stored token file ~/.ragent/github_token

/github login runs the OAuth device flow.

Syntax

```
/github
/github login
/github logout
/github status
/github help
```

Options

Form	Description
/github	bare form, no subcommand
/github login	start the OAuth device flow
/github logout	remove stored credentials
/github status	report the current auth state
/github help	print command help

The login device flow

1. The command shows a user code in the message window.
2. A pending dialog opens.
3. The flow polls in the background until authorisation completes or the attempt times out.
4. On timeout the dialog reports:

Device flow timed out - please try /github login again.

logout removes stored credentials. status reports the current auth state.

Examples

Bare form:

```
/github
```

Start the device flow:

```
/github login
```

Check the auth state:

```
/github status
```

Remove stored credentials:

```
/github logout
```

Output

- `login` shows the user code and opens the pending dialog; completion and failure arrive via the dialog.
- `status` prints whether a token is loaded.

Notes

- The stored token lives in `~/.ragent/github_token`; `logout` removes stored credentials.
- `/reverse` fetches repos through the GitHub API.

Related

- `/gitlab` - the GitLab counterpart
- `/reverse` - uses the GitHub API