

/inbox

Triage inbox findings left by stateful cron jobs

Overview

The inbox collects findings from stateful cron jobs that use the <inbox> tag protocol. Findings are stored in a global JSONL file shared across all sessions, so a scheduled nightly job can leave a note that any later session can read, claim, and act on.

Entries move through statuses: pending entries can be claimed (picked up for work) or dismissed (dropped without action). `clear` empties the inbox.

Syntax

```
/inbox list
/inbox claim <entry_id>
/inbox dismiss <entry_id>
/inbox clear
/inbox help
```

Options / Subcommands

Form	Description
<code>list</code>	Show all inbox entries with IDs, sources, and statuses
<code>claim <entry_id></code>	Mark an entry as claimed
<code>dismiss <entry_id></code>	Mark an entry as dismissed
<code>clear</code>	Remove every finding from the inbox
<code>help</code>	Show the subcommand table and the <inbox> tag protocol note

Examples

```
From: /inbox list
# | ID | Source | Status | Content (60-char preview)
Empty inbox prints:
Inbox is empty. Findings are added by stateful cron jobs that use the
`<inbox>` tag protocol.

From: /inbox list
| 1 | a1b2c3d4 | cron/nightly | pending | Flaky test test_render_cost_scaling failed 3x...
1 finding(s) in inbox.

From: /inbox claim a1b2c3d4
[ok] Entry `a1b2c3d4` marked as claimed.

From: /inbox dismiss a1b2c3d4
[clr] Entry `a1b2c3d4` marked as dismissed.

From: /inbox dismiss nosuchid
[warn] Entry `nosuchid` not found in inbox.
```

```
From: /inbox clear  
[clr] Cleared 4 finding(s) from the inbox.
```

Output

`list` renders a table with the 8-character entry ID, source, status, and a 60-character content preview, ending with `N finding(s) in inbox`. Claim and dismiss print a one-line `[ok]/[clr]` confirmation. Clearing prints the removed count. Unknown IDs print `[warn] Entry ... not found in inbox`. Statuses land in the status bar (`inbox: list`, `inbox: claimed`, and so on).

Related

- `/cron` - scheduled runs that write inbox findings
- `/task` - move a claimed finding into the session task list