

/cron

Schedule, inspect, and manage recurring agent runs (cron events)

Overview

/cron manages scheduled agent runs. An event pairs an agent type with a schedule expression and a prompt; the scheduler fires the event and runs the agent with that prompt. Events persist in the storage database, so schedules survive restarts. Each run's outcome is recorded in a cron log that /cron log can display.

The prompt argument must be enclosed in double quotes. Schedules are parsed by `ragent_types::parse_schedule` and stored with `storage.insert_cron_event`.

Syntax

```
/cron add <cronname> <agent> <schedule> "<prompt>"
/cron remove <cronname>
/cron enable <cronname>
/cron disable <cronname>
/cron list
/cron detail <cronname>
/cron log [event_id]
/cron help
```

Options / Subcommands

Form	Description
add <cronname> <agent> <schedule> "<prompt>"	Create a scheduled event (bare /cron shows the same add form)
remove <cronname>	Delete a scheduled event permanently
enable <cronname>	Re-enable a disabled event
disable <cronname>	Stop an event from firing without deleting it
list	Render a table of all events
detail <cronname>	Show every stored field of one event, prompt untruncated
log [event_id]	Show recent cron run history, optionally for one event
help	Print the schedule grammar and subcommand table

Schedule grammar

Form	Example	Description
at <timestamp>	at 2026-01-15T09:00:00Z	One-shot run at an ISO-8601 timestamp
at <natural time>	at 5pm tomorrow	One-shot run at a natural-language time
from <ts> every <dur>	from 9am every 30m	Repeating, starting at the given time
every <duration>	every 6h	Repeating from now

Timestamps accept ISO-8601 or natural language (5pm, 5:30pm, 17:00, 5am tomorrow). Durations use <int><unit> with units m (minutes), h (hours), d (days), w (weeks), and mo (months).

Examples

From: /cron add nightly-tidy coder "at 2am" "Review yesterday's changes and update the changelog
Creates event nightly-tidy with agent coder, one-shot at 02:00.

From: /cron add hourly-scan explore "every 1h" "Check for new failing tests and report."
Every duration form: repeats hourly from now.

From: /cron add weekday-brief general "from 9am every 1d" "Summarise open tasks."
Repeating daily, first fire at 09:00 today.

From: /cron list
| ID | Agent | Schedule | Enabled | Next due | Prompt |
Renders one row per event; prints "No scheduled events." when none exist.

From: /cron detail nightly-tidy
Every stored field, including the full untruncated prompt.

From: /cron log
| Timestamp | Event | Agent | Outcome | Prompt |
Recent runs of any event; pass an id to narrow: /cron log hourly-scan.

An unquoted prompt is rejected with [warn] The prompt must be enclosed in double quotes.

Output

add prints a Field/Value table (ID, Agent, Schedule, Next due, Prompt). list prints the ID/Agent/Schedule/Enabled/Next due/Prompt table. enable/disable/remove print one confirmation line. log prints the Timestamp/Event/Agent/Outcome/Prompt table read from the cron log.

Related

- /inbox - findings produced by stateful cron runs
- /task - session task tracking
- ragent-tools-core cron logging (read_cron_log)