

/new

Scaffold a new project: `/new --language --type [--stack ] [--github | --gitlab] | /new help`

Overview

`/new` scaffolds a new project in the current directory, which must be empty. The scaffold consists of:

- The ragent workspace: `.ragent/`, `specs/`, `log/`, `.gitignore`, `AGENTS.md`
- A runnable hello-world artifact set for 26 application languages (rust, python, go, typescript, shell, ...) with `library`, `cmdline`, `tui`, and `gui` layouts
- Sample-document stubs for 20 data and DSL formats (json, yaml, sql, cmake, maven, ...) covering every codeindex scanner language
- Optional stack layers via `--stack <name>`
- Starter documentation: `README.md`, `QUICKSTART.md`, `STATS.md`, `docs/`
- Git initialisation with an initial commit
- Optional GitHub or GitLab repository creation and push via `--github / --gitlab`

The command runs on a foreground worker thread: no sub-agent is spawned and no LLM turn is consumed. Progress streams live in the message window.

Syntax

```
/new --language <lang> --type <type>
/new --language <lang> --type <type> --stack <name>
/new --language <lang> --type <type> --github
/new --language <lang> --type <type> --gitlab
/new help
```

Options

Option	Description
<code>--language <lang></code>	Language id. 46 canonical ids are accepted, including aliases such as <code>sh -> shell</code> and <code>yaml -> yaml</code>
<code>--type <type></code>	Layout: <code>library</code> , <code>cmdline</code> , <code>tui</code> , <code>gui</code> , or <code>webapp</code> . Data and DSL languages degrade to manifest-only scaffolds
<code>--stack <name></code>	Optional stack layer. Rust stacks: <code>axum</code> , <code>warp</code> , <code>raylib</code> , <code>gtk4</code> , <code>ratatui</code>
<code>--github</code>	Create a private GitHub repository, set it as origin, and push
<code>--gitlab</code>	The same flow for GitLab. <code>--github</code> and <code>--gitlab</code> are mutually exclusive
<code>help</code>	Print the on-screen option summary

Language and layout notes

- Application languages produce a runnable hello-world artifact set.
- Data and DSL languages produce sample-document stubs instead of runnable code, and their scaffolds degrade to manifest-only.
- The stub set covers every codeindex scanner language.

Examples

Scaffold a Rust command-line project:

```
/new --language rust --type cmdline
```

Scaffold a Rust TUI project with the ratatui stack:

```
/new --language rust --type tui --stack ratatui
```

Scaffold a Python library:

```
/new --language python --type library
```

Scaffold a Rust command-line project and host it on GitHub:

```
/new --language rust --type cmdline --github
```

Scaffold a Go command-line project and host it on GitLab:

```
/new --language go --type cmdline --gitlab
```

Run `/new help` for the on-screen option summary.

Output

The worker thread streams progress lines and updates them in place each frame:

- [..] <step> - step in progress
- [ok] <step> - step completed
- [fail] <step> - step failed

The final summary prints as From: `/new`.

Guards

- The current directory must be empty before scaffolding starts.
- The emitter never silently overwrites existing files.

Related

- Howto manual: `docs/howtos/newproj.md`
- `/spec` - spec lifecycle commands; `/spec reverse --create` chains into `/spec create`
- `/spec reverse` - reverse-engineer a repo and seed a spec