

Tools — Utility

Introspection of the running ragent binary, the active LLM connection, and the host environment.

Tool	Description
<code>model_info</code>	Report the active provider/model, capabilities, context window, and cost tier.
<code>ragent_info</code>	Report the running ragent version, build time, git commit, and compiler.
<code>os_info</code>	Report read-only host OS and hardware introspection (also <code>/osinfo show</code>).
<code>tool_info</code>	Dump the whole tool registry as JSON (name, description, schema, permission category, source).
<code>commands_info</code>	Dump the slash-command catalog as JSON (built-in TUI commands plus plugin-contributed ones).

`model_info`

Report the active provider/model pair, provider display name, capabilities, context window, max output tokens, cost tier, and thinking support. When the Model Router is active, also reports whether routing is enabled and that the effective downstream model is chosen per request.

Arguments

Argument	Type	Required	Description	Typical value
<code>format</code>	enum	no	<code>text</code> (human-readable markdown, default) or <code>json</code> (structured metadata only)	<code>"text"</code>

Example:

```
model_info
model_info format="json"
```

`ragent_info`

Report build and version information about the running ragent binary: the ragent version, the build timestamp, the git commit it was built from (best-effort), and the compiler version. Read-only and offline — it never shells out or hits the network — so the LLM can answer “which version am I running?” directly.

Arguments

Argument	Type	Required	Description	Typical value
format	enum	no	text (human-readable markdown, default) or json (structured metadata only)	"text"

Example:

```

regent_info
regent_info format="json"

```

os_info

Report read-only information about the host operating system and hardware: OS identity and Linux distribution, CPU, graphics adapters and graphics-API versions, physical hardware (system/chassis/motherboard/BIOS identity, storage devices, network interfaces), memory, uptime, and the regent process environment. It always succeeds, reporting unknown/0 placeholders for any value the host cannot supply, and never reads serial numbers, UUIDs, or asset tags. Also available as the `/osinfo show slash` command.

By default (`probe = true`) it runs a fixed, timeout-bounded allowlist of vendor graphics diagnostics (`vulkaninfo`, `glxinfo`, `nvidia-smi`, `rocm_info`, `system_profiler`) so every graphics API is reported with its version - OpenGL, OpenGL ES, and Mesa expose no read-only version file. Those diagnostics only read host state; set `probe: false` for a fully process-free pass.

Arguments

Argument	Type	Required	Description	Typical value
format	enum	no	text (human-readable markdown, default) or json (structured metadata only)	"text"
probe	bool	no	Run the allowlisted graphics diagnostics (default true); false for a process-free report	false

Example:

```

os_info
os_info format="json" probe=false

```

tool_info

Return a JSON-encoded dump of the tool registry: every registered tool with its name, description, parameters JSON schema, permission category, source (`internal` / `mcp:<server>` / `plugin:<id>` / `visibility:<family>`), and hidden state, plus MCP server/tool provenance for bridged tools. Read-only, permission category `none`, hardwired auto-approved.

Arguments

None.

Example:

`tool_info`

commands_info

Return a JSON-encoded catalog of every slash command — the built-in TUI commands (trigger, description, subcommands, flags) plus the commands contributed by enabled plugins, resolved live at call time. Read-only, permission category `none`, hardwired auto-approved.

Arguments

None.

Example:

`commands_info`