/editlog

Edit-operation logging: /editlog on|off|status|show|analyse|clear

Overview

`/editlog` manages the edit-operation log, a record of every file-edit tool call (read, Write, Edit, multiedit, patch, apply_patch, …) and whether it succeeded. Use it to diagnose why edits keep failing: `show` summarises per-tool success rates and `analyse` inspects the failed `old_str` values to characterise why they missed.

Syntax

```
/editlog            Print the help table (same as /editlog help)
/editlog on         Enable edit-operation logging
/editlog off        Disable edit-operation logging
/editlog status     Show enabled state and log directory
/editlog show       Per-tool statistics table
/editlog analyse    Failed old_str analysis
/editlog clear      Empty the edit-log files (files kept)
/editlog help       Print the help table
```

Options / Subcommands

Form	Description
`on`	Enable edit-operation logging via `persist_edit_log`.
`off`	Disable edit-operation logging.
`status`	Show whether logging is enabled and where the log lives (`log/`).
`show`	Render a per-tool table: tool name, total calls, successes, failures, success percentage, plus the recorded failure reasons.
`analyse`	Characterise the failed `old_str` values (risk traits, per-tool failure ratios, most common failure combinations, sample examples).
`clear`	Empty the edit-log files without deleting them; reports the number of cleared entries.
`help`	Print the help table.

`--help` and `-h` are accepted as aliases of `help`.

Examples

`/editlog on`

Starts recording every edit operation.

`/editlog status`

Confirms logging is enabled and prints the `log/` directory used.

`/editlog show`

Shows a table such as:

```
Tool         Calls  OK  Fail   Pct
edit           142  130   12    92
multiedit       38   33    5    87
```

`/editlog analyse`

Reports the risk characteristics of failed `old_str` blocks: per-tool failure ratios, the most common failing combinations (top 10), and concrete examples.

`/editlog clear`

Empties the log files and prints the cleared-entry count; the files remain so future stats continue to accumulate.

`/editlog help`

Prints the table above.

Output

`on`/`off` confirm the state change; a failed persist is reported as a `[warn]` line. `status` prints enabled/disabled plus the directory. `show` prints a fixed-width per-tool stats table with success percentages and the failure reasons seen. `analyse` prints a breakdown of failed `old_str` characteristics, per-tool ratios, top combinations, and examples. `clear` prints how many entries were emptied.

Related

- `/editlog` statistics are cleared by `/log clear editlog`.
- `/log` – log panel and directory clearing.
- `log/editlog/` – where the edit log is written.