

Slash Command Howtos

Per-command reference documents for the ragent TUI slash commands. Each document describes the command, every subcommand and option the dispatcher implements, and worked examples. Typing / in the TUI opens the autocomplete menu, and /<command> help prints per-command help where the handler supports it.

Commands

Command	Document	Summary
/about	about	Show application info, version, and authors
/agent	agent	Switch the active agent: /agent [] /agent help
/agents	agents	List all agents - built-in and custom
/browse_refresh	browse_refresh	Refresh the @ file-picker project index
/bench	bench	Benchmark runner: /bench list init show run status open last cancel
/clear	clear	Clear message history for the current session
/clip	clip	Copy the rendered message-window contents to the system clipboard
/cancel	cancel	Cancel a background task (/cancel /cancel help)
/config	config	Configuration: /config show save list help
/context	context	Manage context cache: /context refresh /context help
/cron	cron	Schedule agent runs: /cron add "" re-move enable disable list log help
/compact	compact	Summarise and compact the conversation history
/inbox	inbox	Triage inbox: /inbox list claim dismiss clear help
/cost	cost	Show session token usage and estimated cost
/help	help	Show available slash commands
/history	history	Browse and re-use previous inputs; /history [filter] restricts to matching entries (arrow keys to select, Enter to insert); /history help

Command	Document	Summary
/inputdiag	inputdiag	Dump input/cursor/selection diagnostics for troubleshooting
/log	log	Log panel: /log [clear sub-agents panics research editlog help]
/loop	loop	Goal-driven agent loop: /loop opens setup, /loop starts, /loop help shows usage
/profile	profile	Toggle the agent-loop profiler panel (/profile on off help)
/perf	perf	Alias for /profile - toggle the agent-loop perf panel (/perf on off help)
/llmstats	llmstats	Show average LLM response time and token throughput
/model	model	Switch the active model, or show metadata with /model show (/model help for usage)
/thinking	thinking	Switch the current thinking level: /thinking auto off low medium high
/provider	provider	Change provider, show config, or configure model router: /provider [show router help]
/provider_reset	provider_reset	Reset the current provider and remove stored credentials
/quit	quit	Exit ragent
/reload	reload	Reload customizations (/reload [all config mcp skills agents])
/resume	resume	Resume the agent from where it was halted (/resume help)
/system	system	Override the agent system prompt (/system /system help)
/template	template	List and apply reusable prompt templates: /template [name] [args]
/goal	goal	Goal-based autonomous stop: /goal set clear show test
/gcf	gcf	Toggle GCF encoding of tool results: /gcf on off show help
/tools	tools	Toggle tool visibility: /tools [office
/skills	skills	List all registered skills and their descriptions (/skills help)
/mcp	mcp	MCP servers: /mcp [status] /mcp discover /mcp connect /mcp disconnect /mcp help

Command	Document	Summary
/task	task	Toggle the TASKS side panel, or list/help tasks: /task [list help]
/team	team	Team management (/team help status show [name]) create/open/delete close message tasks clear cleanup)
/swarm	swarm	Auto-decompose a goal into parallel subtasks (/swarm /swarm status /swarm help)
/bash	bash	Manage bash command lists: /bash add remove allow deny [-global] show help
/dirs	dirs	Manage directory/file permission lists: /dirs add remove allow deny [-global] show help
/yolo	yolo	Toggle YOLO mode - bypass all command validation and tool restrictions (/yolo help)
/spec	spec	Specification management: /spec create add delete list search validate status task govcreate help
/plugins	plugins	Plugin management: /plugins list [-verbose] add [-force] remove enable disable test help
/research	research	Research system: /research create [-mode tiered supervisor competitive] [-summarization-model] [-evaluate] [other flags] <topic...> list open search show delete archive cluster
/reverse	reverse	Reverse-engineer a GitHub repo: /reverse <owner/repo URL> [-tech] [-create]
/new	new	Scaffold a new project: /new -language -type [-stack] [-github -gitlab] /new help
/autopilot	autopilot	Autonomous operation: /autopilot on [-max-tokens N] [-max-time N] off status help
/plan	plan	Delegate planning to the plan agent: /plan
/mode	mode	Set agent role mode: /mode architect coder reviewer debugger tester off help

Command	Document	Summary
/memory	memory	Memory panel (Alt+M): /memory /memory show /memory init /memory read /memory search
/github	github	GitHub integration: /github login logout status help
/gitlab	gitlab	GitLab integration: /gitlab setup logout status help
/update	update	Check for or install updates: /update /update install /update help
/doctor	doctor	Run system diagnostics (providers, git, ripgrep, MCP, memory); /doctor help for details
/webapi	webapi	Manage the HTTP REST API: /webapi enable disable help
/websearch	websearch	Web search engine diagnostics: /websearch show test help
/init	init	Analyse the project and write a summary, or create a default config: /init [config help]
/codeindex	codeindex	Manage codebase index: /codeindex on off show lang reindex rebuild graph <build export lang> explain path communities godnodes help
/status	status	Show status message history: /status [clear]
/mouse	mouse	Toggle mouse support: /mouse on off help
/telemetry	telemetry	Telemetry management: /telemetry help on off setup counters
/telemetry_panel	telemetry_panel	Toggle the telemetry side panel (Alt+O alias); use /telemetry counters to list values
/router	router	Model router management: /router on off status tiers weights boundaries test stats reload he
/startup	startup	Show startup timing breakdown for the current session
/editlog	editlog	Edit-operation logging: /editlog on off status show analyse clear
/actionloop	actionloop	Agent action-loop timing: /actionloop [help clip]

Command	Document	Summary
/bug-report	bug-report	Generate diagnostic bug report with redacted session data (output to log/)
/triggers	triggers	Manage trigger rules: /triggers [list enable disable remove status help]
/undo	undo	Remove the last user/assistant turn pair from the conversation (/undo help)
/name	name	Set a human-readable display name for the session: /name /name help
/alog	alog	Activity log: /alog help on off config list status delete -yes export -yes
/toolchain	toolchain	Language toolchain report: /toolchain list [lang] [-json] /toolchain help
/prompt	prompt	Agent system-prompt inspector: /prompt help primary [agent] subagent [agent] list
/blueprints	blueprints	List installed team blueprints: /blueprints help list

Aliases

Alias	Canonical
/exit	/quit (single dispatch arm "quit" "exit")
/teams	/team (single dispatch arm "team" "teams")
/compress	/compact (deprecated alias; logs a deprecation notice)