

/bug-report

Generate a bug report file with session diagnostics, logs, and transcript

Overview

`/bug-report` writes a self-contained markdown bug report under the project working directory so it can be attached to an issue. The file is created at `log/bug-report-<YYYYMMDD>-<HHMMSS>.md` (the `log/` directory is created if missing). Sensitive content is redacted: log entries and the transcript pass through `redact_secrets`, and transcript messages are truncated.

There are no subcommands; the command runs immediately.

Syntax

`/bug-report`

Options / Subcommands

Form	Description
(bare)	Write the bug report and print its path

Report contents

Section	What it contains
Session Information	Session id, title, directory, created/updated timestamps
Agent Configuration	Active agent, its description, selected model
Tool Configuration	Visible tool count and per-family visibility (office, github, gitlab, teams, agents, plan, codeindex)
Token Usage	Input, output, and total token counts for the session
Recent Log Entries	Last 50 log lines, <code>redact_secrets</code> applied
Session Transcript	Each message, redacted, truncated to 501 characters

Examples

From: `/bug-report`
Bug report written to `log/bug-report-20260911-141530.md`

The report includes session info, agent and tool configuration, token usage, the last 50 log entries, and the session transcript.
Please review the report for sensitive information before sharing.

From: `/bug-report`
(In a session with 3 messages and one tool error)
The transcript section shows each message redacted and truncated to 501 characters; the log section shows the tool error with secrets redacted.

Output

One success block in the message window: the written file path, a summary of what the report includes, and a warning to review the file for sensitive information before sharing it. Failures (unwritable path) print a [warn] error line.

Related

- `/doctor` - live environment diagnostics instead of a file report
- `/debug` - reads session debug logs in-session
- Log directory `log/` also holds sub-agent reports