

/editlog

Edit-operation logging: /editlog on|off|status|show|analyse|clear

Overview

/editlog manages the edit-operation log, a record of every file-edit tool call (read, write, edit, multiedit, patch, apply_patch, ...) and whether it succeeded. Use it to diagnose why edits keep failing: show summarises per-tool success rates and analyse inspects the failed old_str values to characterise why they missed.

Syntax

/editlog	Print the help table (same as /editlog help)
/editlog on	Enable edit-operation logging
/editlog off	Disable edit-operation logging
/editlog status	Show enabled state and log directory
/editlog show	Per-tool statistics table
/editlog analyse	Failed old_str analysis
/editlog clear	Empty the edit-log files (files kept)
/editlog help	Print the help table

Options / Subcommands

Form	Description
on	Enable edit-operation logging via persist_edit_log.
off	Disable edit-operation logging.
status	Show whether logging is enabled and where the log lives (log/).
show	Render a per-tool table: tool name, total calls, successes, failures, success percentage, plus the recorded failure reasons.
analyse	Characterise the failed old_str values (risk traits, per-tool failure ratios, most common failure combinations, sample examples).
clear	Empty the edit-log files without deleting them; reports the number of cleared entries.
help	Print the help table.

--help and -h are accepted as aliases of help.

Examples

/editlog on

Starts recording every edit operation.

/editlog status

Confirms logging is enabled and prints the log/ directory used.

/editlog show

Shows a table such as:

Tool	Calls	OK	Fail	Pct
edit	142	130	12	92
multiedit	38	33	5	87

`/editlog analyse`

Reports the risk characteristics of failed `old_str` blocks: per-tool failure ratios, the most common failing combinations (top 10), and concrete examples.

`/editlog clear`

Empties the log files and prints the cleared-entry count; the files remain so future stats continue to accumulate.

`/editlog help`

Prints the table above.

Output

`on/off` confirm the state change; a failed `persist` is reported as a `[warn]` line. `status` prints enabled/disabled plus the directory. `show` prints a fixed-width per-tool stats table with success percentages and the failure reasons seen. `analyse` prints a breakdown of failed `old_str` characteristics, per-tool ratios, top combinations, and examples. `clear` prints how many entries were emptied.

Related

- `/editlog` statistics are cleared by `/log clear editlog`.
- `/log` – log panel and directory clearing.
- `log/editlog/` – where the edit log is written.