

/log

Log panel: /log [clear subagents|panics|research|editlog|help]

Overview

/log controls the log side panel and the on-disk log files. Invoked with no arguments it toggles the log panel: other side panels (profile, tasks, memory, telemetry) are dismissed and the buffered log-window history is spooled into the panel. With the `clear` subcommand it empties one of the five log directories that the agent writes to under `log/`.

Syntax

```
/log                Toggle the log side panel
/log clear <name>   Clear one log directory
/log help           Print the usage table
```

Options / Subcommands

Form	Description
(bare)	Toggle the log side panel on/off.
<code>clear subagents</code>	Empty <code>log/subagents/</code> (background agent reports).
<code>clear panics</code>	Empty <code>log/panics/</code> .
<code>clear research</code>	Empty <code>logs/research/</code> (note the plural top-level directory).
<code>clear editlog</code>	Empty <code>log/editlog/</code> .
<code>clear logwindow</code>	Empty <code>log/logwindow/</code> .
<code>help</code>	Print the usage table.

Unknown subcommands print the usage text.

Examples

```
/log
```

Toggles the log panel. If it was closed it opens and the panel history is spooled; if it was open it closes.

```
/log clear subagents
```

Empties `log/subagents/` so old background-agent reports no longer consume disk.

```
/log clear research
```

Empties `logs/research/`. This is the only `clear` target that maps to the plural `logs/` root rather than `log/`.

```
/log clear editlog
```

Empties `log/editlog/`. The files are kept (emptied), so subsequent `edit-log` stats in `/editlog` show restart from zero.

```
/log clear logwindow
```

Empties `log/logwindow/`, removing accumulated TUI log-window session logs.

`/log help`

Prints the subcommand table shown above.

Output

Bare invocation shows or hides the log side panel; when opening, any other side panel (profile, tasks, memory, telemetry) is dismissed and the buffered log-window history is spooled into the panel. `clear` reports which directory was emptied. `help` prints the table of valid clear targets.

Related

- `/editlog` – edit-operation statistics (the `editlog clear` target).
- `/profile`, `/memory`, `/telemetry` – side panels dismissed when the log panel opens.
- `log/` directory layout: `log/subagents/`, `log/panics/`, `log/editlog/`, `log/logwindow/`, and `logs/research/`.