

/agent

Switch the active agent: `/agent []` | `/agent help`

Overview

`/agent` controls which agent preset drives the session. With no argument it opens the interactive agent picker dialog, which lists every cycleable agent (built-in and custom, custom entries flagged) and lets you choose one with the keyboard. With a name argument it switches directly to that agent without opening any dialog, logging the switch and publishing an `AgentSwitched` event on the session event bus.

Unknown names are rejected with a status-bar message listing the available agent names. `/agent help` prints a small subcommand table instead of acting.

Syntax

```
/agent          # open the interactive agent picker
/agent <name>   # switch directly to a named agent
/agent help     # show the subcommand table
```

Options / Subcommands

Form	Description
<code>/agent</code>	Open the interactive agent picker
<code>/agent <name></code>	Switch directly to a named agent (e.g. <code>coder</code> , <code>general</code> , <code>architect</code>)
<code>/agent help</code>	Show the <code>/agent help</code> table

Notes:

- The picker lists only `cycleable_agents` (agents reachable via agent cycling); custom agents are included when they are cycleable and are marked with a `[custom]`-style flag in the picker data.
- A successful direct switch updates the current agent index, agent name, and agent info, writes an Info log line (Switched to: `<name>` (`<description>`)), and publishes `Event::AgentSwitched` when a session is active.

Examples

```
/agent
```

```
/agent coder
```

Switch with confirmation in the log:

```
Switched to: coder (Full-stack coding agent with file and shell access)
```

```
/agent architect
```

```
/agent help
```

Unknown agent feedback (status bar + warn log):

Unknown agent 'foo'. Available: general, coder, task, architect, ask, debug, code-review, orchest

Output

- `/agent` opens the agent picker dialog (no message emitted).
- `/agent <name>` on success sets the status bar to `agent: <name>` and logs the switch; on failure the status bar shows the unknown-agent message and a Warn log entry is written.
- `/agent help` appends an assistant bubble From: `/agent help` containing the subcommand table; status shows `agent: help`.

Related

- `/agents` - list every built-in and custom agent with descriptions
- `/model` - switch the active LLM model
- `/help` - list all available slash commands