

/config

“Inspect, back up, and restore ragent configuration” (SlashCommandDef, crates/ragent-tui/src/app/state.rs).

Overview

/config is the in-TUI configuration inspector and backup manager. The show form renders the resolved configuration without launching the agent: where the application stores its files, which config files were found on disk, and the final merged value of every key together with the source that supplied it. The save form writes a timestamped backup of the global configuration into the config_dir/saves/ directory, and the list form opens an interactive picker over previously saved backups so one can be restored.

Handlers live in crates/ragent-tui/src/app/slash.rs (the config arm, approximately lines 2238-2652). All output accumulates under a From: /config header in the message window.

Syntax

```
/config show
/config save
/config list
/config help
```

Bare /config behaves like the unknown-args case and prints the usage line.

Options / Subcommands

Form	Description
/config show	Render application paths, discovered config files, and the fully resolved configuration table
/config save	Back up the global config to a timestamped file under config_dir/saves/
/config list	List saved configuration backups and open the restore picker
/config help	Show the subcommand summary

Examples

Inspect resolved configuration

```
/config show
```

Output (representative, condensed):

From: /config show

Application Paths

```
Working directory: /home/user/Projects/ragent
Data directory:   ~/.local/share/ragent
Config directory: ~/.config/ragent
```

Config Files

Path	Exists
/home/user/Projects/ragent/.ragent/ragent.json	yes
/home/user/.config/ragent/ragent.json	no
\$RAGENT_CONFIG	(unset)

Resolved Values

key	source	value
...		

Back up the global configuration

/config save

Output:

From: /config save

[ok] Configuration backed up to /home/user/.config/ragent/saves/ragent.json.20260911-101500

If the backup cannot be written the command reports [err] with No changes were made. and leaves the configuration untouched.

List and restore a saved configuration

/config list

Output (picker state):

From: /config list

Saved configurations (newest first):

1. ragent.json.20260911-101500
2. ragent.json.20260910-183022

...

With no saved backups present the output is:

From: /config list

No saved configurations found

Hint: use /config save to create a backup

Show the subcommand summary

/config help

Output:

From: /config help

/config show | /config save | /config list | /config help

Output

/config show sections

- **Application Paths** - working directory, data directory, and config directory currently in use.

- **Config Files** - a table with exists checks for the project config (<cwd>/`.ragent/ragent.json`), the global config (<config_dir>/`ragent.json`), and the path given by the `RAGENT_CONFIG` environment variable.
- **Resolved Values** - a key | source | value table. Precedence is: defaults < global config < project config < env file < `RAGENT_CONFIG_CONTENT`. Every row names the source that supplied the winning value.
- **Union fields** - the merged-map fields permission, instructions, skill_dirs, hooks, bash, hidden_tools, yolo, edit_log, sdd, piegap, and experimental are labelled global + project (union) when a value is set in both layers.
- **Secret redaction** - keys matching `*_api_key` / `*_key`, plus the `openalex_email`, `gitlab`, `gmail`, and `channels` sections, are redacted before display.
- **Storage** - the resolved SQLite database path.
- **Code Index** - the index directory `.ragent/codeindex`.
- **Memory** - project and global memory directories.
- **Custom Agents** - the custom agent directories being scanned.

`/config save`

Emits [ok] with the backup path, or [err] with `No changes were made.` when the backup could not be written.

`/config list`

Scans <config_dir>/`saves/` for files matching `ragent.json.*` (excluding `.tmp` candidates), sorts newest-first by modification time, and opens the `ConfigSavePickerState` interactive picker. In the picker:

- Up / Down or k / j move the selection,
- Enter restores the selected snapshot,
- Esc cancels.

An empty directory produces `No saved configurations found` plus the `/config save` hint.

Unknown arguments

Prints the usage line `/config show | /config save | /config list | /config help`.

Related

- `/init config` - write a fresh default config file to disk
- `/reload` - re-read `ragent.json` into the running session
- `/skills` - view the skill registry loaded from `skill_dirs`
- `QUICKSTART.md` - configuration examples
- `SPEC.md` - full configuration schema