

/name

“Set a human-readable display name for the session: /name | /name help” (SlashCommandDef, crates/ragent-tui/src/app/state.rs).

Overview

/name assigns a display name to the active session (FR-015). The name is persisted in session metadata through the storage layer, so it appears in session lists and survives restarts and resume operations. Calling /name with no argument clears the existing name. Use it to label long-running work sessions so they are easy to find later in /session list.

The handler is the name arm in crates/ragent-tui/src/app/slash.rs (lines 5855-5913).

Syntax

```
/name <display-name>
/name
/name help
```

Options / Subcommands

Form	Description
/name <display-name>	Set a human-readable name for the active session (persists in session metadata)
/name	Clear the session name
/name help	Show the help table

Examples

Name the session

```
/name compaction-benchmarks
```

Status line:

Session name set to 'compaction-benchmarks'

Log entry: Session name set to 'compaction-benchmarks'.

Clear the session name

```
/name
```

Status line:

Session name cleared

Log entry: Session name cleared.

Show help

/name help

Output:

From: /name help

/name - Session display name

Subcommand	Description
`/name <display-name>`	Set a human-readable name for the active session (persists in session)
`/name`	Clear the session name
`/name help`	Show this help

Storage failure

If the underlying storage update fails, the status line shows [warn] Failed to set session name: <error> (or [warn] Failed to clear session name: <error>) and the log records the error.

Output

- Success (name set): status Session name set to '<name>' plus an Info log entry.
- Success (name cleared): status Session name cleared plus an Info log entry.
- No active session: status [warn] No active session to name.
- Storage error: [warn] Failed to set/clear session name: <error> plus an Error log entry with the same text.

The name is written through `storage.update_session(&session_id, name)`; an empty name argument is the clear path and passes an empty string.

Related

- /session list - see named sessions in the list
- /session resume - resume a named session by id
- /quit - leave the session (the name persists for next time)