/cron

Schedule, inspect, and manage recurring agent runs (cron events)

Overview

`/cron` manages scheduled agent runs. An event pairs an agent type with a schedule expression and a prompt; the scheduler fires the event and runs the agent with that prompt. Events persist in the storage database, so schedules survive restarts. Each run's outcome is recorded in a cron log that `/cron log` can display.

The prompt argument must be enclosed in double quotes. Schedules are parsed by `ragent_types::parse_schedule` and stored with `storage.insert_cron_event`.

Syntax

```
/cron add <cronname> <agent> <schedule> "<prompt>"
/cron remove <cronname>
/cron enable <cronname>
/cron disable <cronname>
/cron list
/cron detail <cronname>
/cron log [event_id]
/cron help
```

Options / Subcommands

Form	Description
`add <cronname> <agent> <schedule> "<prompt>"`	Create a scheduled event (bare `/cron` shows the same add form)
`remove <cronname>`	Delete a scheduled event permanently
`enable <cronname>`	Re-enable a disabled event
`disable <cronname>`	Stop an event from firing without deleting it
`list`	Render a table of all events
`detail <cronname>`	Show every stored field of one event, prompt untruncated
`log [event_id]`	Show recent cron run history, optionally for one event
`help`	Print the schedule grammar and subcommand table

Schedule grammar

Form	Example	Description
`at <timestamp>`	`at 2026-01-15T09:00:00Z`	One-shot run at an ISO-8601 timestamp
`at <natural time>`	`at 5pm tomorrow`	One-shot run at a natural-language time
`from <ts> every <dur>`	`from 9am every 30m`	Repeating, starting at the given time
`every <duration>`	`every 6h`	Repeating from now

Timestamps accept ISO-8601 or natural language (`5pm`, `5:30pm`, `17:00`, `5am tomorrow`). Durations use `<int><unit>` with units `m` (minutes), `h` (hours), `d` (days), `w` (weeks), and `mo` (months).

Examples

```
From: /cron add nightly-tidy coder "at 2am" "Review yesterday's changes and update the changelog
Creates event nightly-tidy with agent coder, one-shot at 02:00.
```

```
From: /cron add hourly-scan explore "every 1h" "Check for new failing tests and report."
Every duration form: repeats hourly from now.
```

```
From: /cron add weekday-brief general "from 9am every 1d" "Summarise open tasks."
Repeating daily, first fire at 09:00 today.
```

```
From: /cron list
| ID | Agent | Schedule | Enabled | Next due | Prompt |
Renders one row per event; prints "No scheduled events." when none exist.
```

```
From: /cron detail nightly-tidy
Every stored field, including the full untruncated prompt.
```

```
From: /cron log
| Timestamp | Event | Agent | Outcome | Prompt |
Recent runs of any event; pass an id to narrow: /cron log hourly-scan.
```

An unquoted prompt is rejected with `[warn] The prompt must be enclosed in double quotes.`

Output

`add` prints a Field/Value table (ID, Agent, Schedule, Next due, Prompt). `list` prints the ID/Agent/Schedule/Enabled/Next due/Prompt table. `enable`/`disable`/`remove` print one confirmation line. `log` prints the Timestamp/Event/Agent/Outcome/Prompt table read from the cron log.

Related

- `/inbox` - findings produced by stateful cron runs
- `/task` - session task tracking
- ragent-tools-core cron logging (`read_cron_log`)