# /tools

Toggle tool visibility: /tools [github|gitlab|teams|agents|plan|codeindex|masterfetch] [on|off] | /tools help

## Overview

`/tools` has two behaviours. The bare form (and `/tools show`) prints the tool visibility table - the current on/off state of every visibility switch. With a switch name it reports that switch's state, and with a switch plus a state word it toggles the visibility of that tool family for the session and saves the choice to the active config source.

The implementation accepts seven switches: `github`, `gitlab`, `teams`, `agents`, `plan`, `codeindex` and `masterfetch`. Toggling a switch rewrites `tool_visibility` in the config source and invalidates the session processor's config cache so the change takes effect immediately.

## Syntax

```
/tools                          # show the visibility table (same as: show)
/tools show                     # same as bare form
/tools <switch>                 # read one switch's state
/tools <switch> on|off          # set one switch (enable/disable also accepted)
/tools help                     # usage help (aliases: --help, -h, usage)
```

## Options / Subcommands

| Form | Description |
|---|---|
| `/tools` | Render the tool visibility table |
| `/tools show` | Same as the bare form |
| `/tools <switch>` | Report whether `<switch>` is currently on or off |
| `/tools <switch> on` | Enable the switch (`enable` also accepted) |
| `/tools <switch> off` | Disable the switch (`disable` also accepted) |
| `/tools help` | Print usage help |

Switches (all seven accepted): `github`, `gitlab`, `teams`, `agents`, `plan`, `codeindex`, `masterfetch`.

## Examples

Show the visibility table:

```
/tools
```

Read a single switch:

```
/tools teams
```

Turn the GitHub tool family off for this project:

```
/tools github off
```

Re-enable codeindex tools:

`/tools codeindex on`

Disable the masterfetch tool family:

`/tools masterfetch off`

Print the usage help:

`/tools help`

## Output

Visibility table (bare form): one row per switch with its on/off state.

Single switch read:

`` `teams` is currently **on**. ``

Successful toggle (the config is saved and the config cache invalidated):

`` [ok] `<switch>` visibility is now **on**. ``

Invalid state word:

`[warn] Usage: /tools <switch> on|off`

Config save failure (the in-session change still applied):

`` [warn] `<switch>` visibility changed ... but saving config failed: <error> ``

and the status bar notes `tools: <switch> ... (unsaved)`.

## Related

- `/config show` - inspect the resolved configuration including tool visibility
- `/reload config` - re-read `ragent.json` after manual edits
- `tool_visibility` section in `ragent.json` - persistent equivalent of these switches