/actionloop

Agent action-loop timing: /actionloop [help|clip]

Overview

`/actionloop` prints timing information for the agent action loop – the per-action durations collected by the agent-loop profiler. The bare form prints the report in the message window; `clip` copies the same report to the system clipboard.

Syntax

```
/actionloop            Print the action-loop timing report
/actionloop clip       Copy the timing report to the clipboard
/actionloop help       Print the help table
```

Options / Subcommands

Form	Description
(bare)	Print the timing report, or the no-samples message when profiling has not recorded anything yet.
`clip`	Copy the `actionloop_report()` text to the clipboard. With no recorded samples it prints the no-samples message instead of copying.
`help`	Print the help table.

`--help` and `-h` are accepted as aliases of `help`.

Examples

`/actionloop`

Prints the current timing report. If no samples were recorded it prints the reminder: enable `/profile on` and run the agent.

`/actionloop clip`

Copies the report so it can be pasted into a bug report or review.

`/actionloop help`

Prints the table above.

```
/profile on
/actionloop
```

Typical sequence: enable the profiler panel first so the action loop records samples, then print the report.

Output

Bare form prints the timing report when samples exist; otherwise it prints “Enable `/profile on` and run the agent”. `clip` copies the report and confirms; with no samples it prints the same enable-profiling reminder.

Related

- `/profile` – enable/disable the profiler panel that feeds this report.
- `/perf` – alias of `/profile`.