/gitlab

GitLab integration: /gitlab setup | logout | status | help

Overview

`/gitlab` manages GitLab authentication for the TUI session.

`setup` opens an interactive dialog pre-filled with the existing instance URL (default `https://gitlab.com`) and collects three values:

- Instance URL
- Username
- Personal access token

Syntax

```
/gitlab
/gitlab setup
/gitlab logout
/gitlab status
/gitlab help
```

Options

Form	Description
`/gitlab`	bare form, no subcommand
`/gitlab setup`	interactive dialog for instance URL, username, and personal access token
`/gitlab logout`	delete the stored token and config
`/gitlab status`	report the current auth state
`/gitlab help`	print command help

Setup dialog fields

Field	Description
Instance URL	pre-filled with the existing instance URL; default `https://gitlab.com`
Username	your GitLab username
Personal access token	the token used for GitLab API access

Examples

Open the setup dialog:

```
/gitlab setup
```

Check the auth state:

```
/gitlab status
```

Remove the stored token and config:

```
/gitlab logout
```

Print command help:

```
/gitlab help
```

Output

- `setup` opens the dialog.
- `logout` confirms deletion.
- `status` prints the auth state.

Notes

- The dialog is pre-filled with the existing instance URL; when nothing is stored yet the default is `https://gitlab.com`.
- `logout` deletes both the stored token and the config.
- `setup` can be re-run to update the stored instance URL, username, or token.

Related

- `/github` - the GitHub counterpart
- `/new --gitlab` - scaffold a project and host it on GitLab