# /log

Log panel: /log [clear subagents|panics|research|editlog|help]

## Overview

`/log` controls the log side panel and the on-disk log files. Invoked with no arguments it toggles the log panel: other side panels (profile, tasks, memory, telemetry) are dismissed and the buffered log-window history is spooled into the panel. With the `clear` subcommand it empties one of the five log directories that the agent writes to under `log/`.

## Syntax

```
/log                Toggle the log side panel
/log clear <name>   Clear one log directory
/log help           Print the usage table
```

## Options / Subcommands

| Form | Description |
|---|---|
| (bare) | Toggle the log side panel on/off. |
| `clear subagents` | Empty `log/subagents/` (background agent reports). |
| `clear panics` | Empty `log/panics/`. |
| `clear research` | Empty `log/research/` (web-gather JSONL logs). |
| `clear editlog` | Empty `log/editlog/`. |
| `clear logwindow` | Empty `log/logwindow/`. |
| `help` | Print the usage table. |

Unknown subcommands print the usage text.

## Examples

`/log`

Toggles the log panel. If it was closed it opens and the panel history is spooled; if it was open it closes.

`/log clear subagents`

Empties `log/subagents/` so old background-agent reports no longer consume disk.

`/log clear research`

Empties `log/research/`, removing accumulated web-gather instrumentation logs (`research-<name>-<ts>-<rand>-web.js`

`/log clear editlog`

Empties `log/editlog/`. The files are kept (emptied), so subsequent edit-log stats in `/editlog show` restart from zero.

`/log clear logwindow`

Empties `log/logwindow/`, removing accumulated TUI log-window session logs.

`/log help`

Prints the subcommand table shown above.

## Output

Bare invocation shows or hides the log side panel; when opening, any other side panel (profile, tasks, memory, telemetry) is dismissed and the buffered log-window history is spooled into the panel. `clear` reports which directory was emptied. `help` prints the table of valid clear targets.

## Related

- `/editlog` – edit-operation statistics (the `editlog` clear target).
- `/profile`, `/memory`, `/telemetry` – side panels dismissed when the log panel opens.
- `log/` directory layout: `log/subagents/`, `log/panics/`, `log/editlog/`, `log/logwindow/`, and `log/research/`.