Tools — Web

Simple HTTP fetching and web search. For rich HTML-to-markdown extraction, PDFs, bulk fetches, or envelope signals (`content_ok`, `is_official`, `is_stale`), prefer the MasterFetch tools.

Tool	Description
`webfetch`	Fetch a URL via HTTP GET; HTML converted to text.
`websearch`	Web search returning titles, URLs, snippets.
`http_request`	Full HTTP method/headers/body control.

Use cases: fetching documentation pages, testing APIs, quick scraping.

---

webfetch

Fetch the content of a URL via HTTP GET. HTML is converted to plain text unless `format: "raw"` is requested.

Arguments

Argument	Type	Required	Description	Typical value
`url`	string	yes	URL to fetch (HTTP/HTTPS only)	`"https://rust-lang.org"`
`format`	enum	no	`text` (HTML → text, default) or `raw` (unchanged)	`"text"`
`max_length`	integer	no	Maximum characters returned	`50000`
`timeout`	integer	no	Request timeout in seconds	`30`

Example:

```
webfetch url="https://rust-lang.org"
webfetch url="https://example.com/page.html" format="raw" max_length=10000
```

---

websearch

Search the web and return results with titles, URLs, and snippets. Uses the masterfetch multi-engine pipeline by default (keyless backends; optional Tavily/LangSearch keys improve quality).

Arguments

Argument	Type	Required	Description	Typical value
`query`	string	yes	Search query	`"rust async patterns"`
`num_results`	integer	no	Number of results (default 5, max 20)	`10`

Example:

```
websearch query="tokio spawn_blocking" num_results=10
```

---

http_request

Perform an HTTP request with full control over method, headers, and body. Returns the status code, selected headers, and the body (truncated at 1 MiB).

Arguments

Argument	Type	Required	Description	Typical value
`url`	string	yes	Full URL including scheme	`"https://api.github.com/repos/rust-la`
`method`	enum	no	`GET` (default), `POST`, `PUT`, `PATCH`, `DELETE`, `HEAD`, `OPTIONS`	`"GET"`
`headers`	object	no	Request headers as key/value map. Only a small allow-list is accepted: `accept`, `accept-language`, `content-type`, `user-agent`. Every other header (credentials, routing, hop-by-hop) is refused, so a redirect cannot carry a secret off-origin (SEC-035).	`{"Accept":"application/json"}`
`body`	string	no	Request body (for `POST`/`PUT`/`PATCH`)	`"{\"name\":\"x\"}"`
`timeout`	integer	no	Timeout in seconds	`30`

Example:

```
http_request url="https://api.github.com/repos/rust-lang/rust" method="GET"
http_request url="https://httpbin.org/post" method="POST" body="{\"a\":1}"
```