

## Tools — GitLab

Native GitLab tools for issues, merge requests, pipelines, and jobs. Requires `/gitlab` setup authentication and a GitLab-backed git remote.

| Tool                                | Description              |
|-------------------------------------|--------------------------|
| <code>gitlab_list_issues</code>     | List issues.             |
| <code>gitlab_get_issue</code>       | Get issue details.       |
| <code>gitlab_create_issue</code>    | Create an issue.         |
| <code>gitlab_comment_issue</code>   | Comment on an issue.     |
| <code>gitlab_close_issue</code>     | Close an issue.          |
| <code>gitlab_list_mrs</code>        | List merge requests.     |
| <code>gitlab_get_mr</code>          | Get MR details.          |
| <code>gitlab_create_mr</code>       | Create a merge request.  |
| <code>gitlab_merge_mr</code>        | Merge an MR.             |
| <code>gitlab_approve_mr</code>      | Approve an MR.           |
| <code>gitlab_list_pipelines</code>  | List pipelines.          |
| <code>gitlab_get_pipeline</code>    | Get pipeline details.    |
| <code>gitlab_list_jobs</code>       | List jobs in a pipeline. |
| <code>gitlab_get_job</code>         | Get job details.         |
| <code>gitlab_get_job_log</code>     | Get job log output.      |
| <code>gitlab_retry_job</code>       | Retry a failed job.      |
| <code>gitlab_cancel_job</code>      | Cancel a running job.    |
| <code>gitlab_retry_pipeline</code>  | Retry a pipeline.        |
| <code>gitlab_cancel_pipeline</code> | Cancel a pipeline.       |

**Visibility switch:** `gitlab`.

### `gitlab_list_issues`

#### Arguments

| Argument            | Type   | Required | Description                   | Typical value |
|---------------------|--------|----------|-------------------------------|---------------|
| <code>state</code>  | enum   | no       | opened (default), closed, all | "opened"      |
| <code>labels</code> | string | no       | Comma-separated label names   | "bug"         |

### `gitlab_get_issue` / `gitlab_close_issue`

Get full issue details, or close an issue.

#### Arguments

| Argument | Type    | Required   | Description                        |
|----------|---------|------------|------------------------------------|
| iid      | integer | yes        | Issue internal ID (project-scoped) |
| comment  | string  | no (close) | Closing note posted before closing |

## gitlab\_create\_issue

### Arguments

| Argument    | Type   | Required | Description             | Typical value              |
|-------------|--------|----------|-------------------------|----------------------------|
| title       | string | yes      | Issue title             | "Pipeline failing on main" |
| description | string | no       | Description in markdown | —                          |
| labels      | string | no       | Comma-separated labels  | "bug"                      |

## gitlab\_comment\_issue

| Argument | Type    | Required | Description       |
|----------|---------|----------|-------------------|
| iid      | integer | yes      | Issue internal ID |
| body     | string  | yes      | Comment text      |

## gitlab\_list\_mrs

### Arguments

| Argument      | Type   | Required | Description                           | Typical value |
|---------------|--------|----------|---------------------------------------|---------------|
| state         | enum   | no       | opened (default), merged, closed, all | "opened"      |
| target_branch | string | no       | Filter by target branch               | "main"        |

## gitlab\_get\_mr

| Argument | Type    | Required | Description               |
|----------|---------|----------|---------------------------|
| iid      | integer | yes      | Merge request internal ID |

## **gitlab\_create\_mr**

### **Arguments**

| Argument      | Type   | Required | Description             | Typical value          |
|---------------|--------|----------|-------------------------|------------------------|
| title         | string | yes      | MR title                | "Add greet subcommand" |
| source_branch | string | yes      | Source branch           | "feature/greet"        |
| target_branch | string | yes      | Target branch           | "main"                 |
| description   | string | no       | Description in markdown | —                      |

## **gitlab\_merge\_mr / gitlab\_approve\_mr**

| Argument | Type    | Required | Description               |
|----------|---------|----------|---------------------------|
| iid      | integer | yes      | Merge request internal ID |

## **gitlab\_list\_pipelines / gitlab\_get\_pipeline**

| Argument | Type    | Required  | Description                                 | Typical value |
|----------|---------|-----------|---------------------------------------------|---------------|
| status   | enum    | no (list) | running, pending, success, failed, canceled | "failed"      |
| id       | integer | yes (get) | Pipeline ID                                 | —             |

## **gitlab\_list\_jobs / gitlab\_get\_job / gitlab\_get\_job\_log**

| Argument    | Type    | Required                   | Description               |
|-------------|---------|----------------------------|---------------------------|
| pipeline_id | integer | yes (list_jobs)            | Pipeline to list jobs for |
| job_id      | integer | yes (get_job, get_job_log) | Job ID                    |

gitlab\_get\_job\_log returns the job's trace output (may be large).

## **gitlab\_retry\_job / gitlab\_cancel\_job / gitlab\_retry\_pipeline / gitlab\_cancel\_pipeline**

| Argument    | Type    | Required             | Description |
|-------------|---------|----------------------|-------------|
| job_id      | integer | yes (job tools)      | Job ID      |
| pipeline_id | integer | yes (pipeline tools) | Pipeline ID |

**Example:**

```
gitlab_list_pipelines status="failed"
gitlab_list_jobs pipeline_id=12345
gitlab_get_job_log job_id=67890
gitlab_retry_job job_id=67890
```