

# The Story of Cold Ice - ICETRO





STAINLESS STEEL

Durable stainless steel exterior Durable & Rustless case for long life.

ALL



**AIR FILTER** 

Removable & cleanable air filter to protect condenser from dust and grease. SCI-050

SCI-120A ICI-050V/H

ADJUSTABLE LEGS Levelers standard 0 to 50mm (0' to 2')

Levelers standard 0 to 18mm (0' to 0.7')

SCI-035 SCI-050

SCI-090

SCI-090

SCI-120A

Levelers standard 0 to 115mm (0' to 4.5')

ICI-050V/H



**AIR COOLED** 

No water usage for cooling the condenser \*Ambient temperature range 10°C~43°C

ALL

## **\*\*** SELF-CONTAINED TYPE

#### STORAGE BIN

Each models have it's own storage bin for ice.

#### **CRYSTALICE**

The spray injection type makes individual cubes with unique bell shaped ice.

#### **EASY INSTALLATION**

Just connect electricity, water & drain hose then turn on the machine.







INSULATION

High density Polyurethane foam storage bin keeps ice for long

ALL





Up to 150Kg optional storage bin [SCI-235B] for Modular series.

#### LARGE PRODUCTION

Modular type is suitable for large stores.

#### **EASY OPERATION**

Simple indicator & switch





SCI-300AH

SCI-530AH

SCI-235B STORAGE BIN

MODEL	A25B15	SCI-035	SCI-050	SCI-090	SCI-120A		
Production	30Kg (66Lbs)	32Kg (71Lbs)	48kg (106Lbs)	89Kg (197Lbs)	125Kg (276Lbs)		
Storage Capacity	12Kg (26Lbs)	10Kg (22Lbs)	13Kg (28.7Lbs)	45Kg (99.21Lbs)	45Kg (99.21Lbs)		
Dimension [mm]	378 x 624 x 855	403 × 460 × 757	523 × 635 × 902	758 × 648 × 1,125	750 × 656 × 1,136		
[inch]	14.9 x 24.6 x 33.7	15.9 × 18.2 × 29.8	20.6 × 25.0 × 35.6	29.9 × 25.6 × 44.3	29.6 × 25.9 × 44.8		
Weight	50Kg (110Lbs)	50Kg (110Lbs)	58Kg (128Lbs)	90Kg (199Lbs)	102Kg (225Lbs)		
Compressor	0.35HP/3,300BTU	0.37HP/3,500BTU	0.5HP/4,800BTU	0.75HP/8,200BTU	1.0HP/12,800BTU		
Power consumption	500w	450w	800w	1,100w	1,400w		
Refrigerant	R-134A	R-134A	R-404A	R-404A	R-404A		
Ice cubes	24ea/cycle	24ea/cycle	36ea/cycle	60ea/cycle	60ea/cycle		
Voltage option	115v/60hz/1PH						
	208~230V/60Hz/1PH						
	220~240V/50Hz/1PH						

### **X** VERTICAL TYPE

MODEL	ICI-050V, 050VH	SCI-200A, 200AH	SCI-300A / 300AH	SCI-530A / 530AH	SCI-235B(STORAGE BIN)
Production	43Kg (96Lbs)	210Kg (463Lbs)	310kg (684Lbs)	420Kg (926Lbs)	Ž.
Storage Capacity	13Kg (28.7lbs)	-	-		150Kg (331Lbs)
Dimension [mm]	520 × 570 × 760	762 × 614 × 590	762 × 614 × 590	762 × 614 × 1,180	764 × 780 × 1,050
[inch]	20.5 × 22.5 × 29.9	30.0 × 24.1 × 23.3	30.0 × 24.1 × 23.3	30.0 × 24.1 × 35.5	30.1 × 30.7 × 41.4
Weight	50Kg (111Lbs)	75Kg (166Lbs)	80Kg (177Lbs)	150Kg (331Lbs)	70Kg (154Lbs)
Compressor	0.47HP/4,200BTU	1.0HP/12,800BTU	1.5HP/18,000BTU	2HP/25,600BTU	į.
Power consumption	500w	1,250w	1,300w	2,500w	-
Refrigerant	R-134A		ã		
lce cubes [Full dice]	60ea/cycle		-		
[Half dice]	120ea/cycle		~		
Voltage option	115V/60Hz/1PH				
	2	-			
Remark	Self-Contained Type		52	Two units of SCI-200A combined	5

- · Products' exterior and specification can be modified without prior notice.
- · Operation Requirements

Ambient Temp Range :  $10\,^{\circ}\text{C} \sim 43\,^{\circ}\text{C}$  ( $50\,^{\circ}\text{F} \sim 110\,^{\circ}\text{F}$ ) Water Temp Range :  $10\,^{\circ}\text{C} \sim 32\,^{\circ}\text{C}$  ( $50\,^{\circ}\text{F} \sim 90\,^{\circ}\text{F}$ )

- · All models certified by CE & ETL, ETL SANITATION



Manufactured by:



78BL/3LT, 648-2, Kojan-Dong, Namdong-Ku, Incheon, Korea TEL: +82-32-814-2160 FAX: +82-32-814-1798 Website: www.icerto.com www.icemaker.co.kr E-mail: webmaster@icemaker.co.kr Distributed by: